

		Notes			
	WALLS 230x115mm burnt bricks wall, all walls to be reinforced every 4th course with brick force wire 15mm cement-sand plaster in mix 1:2.Lime patty internally				
WARE te - no plastic (all ceramic) be approved by ent before purchase. s for shower, sink and whb. hirror, coat hooks,toilet roll oap holder	internally: Walls receive 15mm lime putty plaster to smooth steel toweled finish undercoat and 2 coats of wash 'n' wear emulsion color choice to architect/client's approval Internally 15mm cement-sand plaster, lime-putty finish, painted one coat plaster primer and two coats interior quality WASH and WEAR paint to client's choice. -500g/m ² polythene dpc at base				
250 535 600 - 600 - 535 - 00 Store 000 - 600 - 535 - 00 Store 000 - 600	0x500x50mm thick				
l μ μ μ μ μ μ μ μ μ μ μ μ μ μ μ μ μ μ μ	inforced removable e-cast slab with 25mm de slots				
		CHARTERED •Architect • Urban D P.O. Box 32341 Chichiri, Blantyo	e 3, MALAWI	Project Drawing	
		Tel: (+265) 99; email: archartla ⊖ □ □ □ ↓ ↓	PROPOSED REFURBISHMENT TO EXISTING OFFI BLOCK ON PLOT NoALONG INDEPENDENC DRIVE - BLANTYRE		ING OFFICE PENDENCE
		CLIENT	NRB-BLANTYRE DRO		
		TITLE Design Drawing Certified By	SECTIONS Steve Musopole A. Meza Steve Musopole Chartered Architect		
		date	revision(s)	sign.	appr.