REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,00P agrees BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS Bill of Quantities

Item	Description	Unit	Qty	Unit Cost	Amount
No				(Le)	(Le)
1.00	PRELIMINARIES				
1.01	MOBILIZATION				
	The contractor will mobilise and deliver to the				
	site all relevant equipment, personel and				
	materials necessary for the execution of the				
	works	item	1		
1,02	SITE OFFICE/STORE				
1,02	Allow for providing suitable secure store for				
	materials used for the project and also a				
	Temporary secure office on site for the site				
	Foreman-in -charge and other craftsmen	item	1		
	roteman-in -charge and other craftsmen	item	1		
1.03	INSURANCE/LICENSES				
	Provide Insurance against injury to personnel				
	Also make all arrangements for the issue of				
	licenses, permit etc required by law for the				
	executiuon of the contract	item	1		
1.04	PROGRESS PHOTOGRAPHS				
	Progress photographs should be provided				
	in intervals. Number and sizes of the photographs				
	will be directed by the Supervising Engineer or				
	his representative	item	1		
1.05	DEMOBILIZATION				
1.05					
	Allow for the demobilization of all plants equip,ent and personnel and left over materials				
	on work completion. The surrounding within				
	the temporary fence must be thoroughly cleared				
	and cleaned befoe the final inspection and				
	handling over the facilities to the Client.	item	1		
	inanding over the facilities to the cheft.	item	1		
	PRELIMINARIES carried to Summary				

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,00P agre2 BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS Bill of Quantities

Item	Description	Unit	Qty	Unit Cost	Amount
No				(Le)	(Le)
	Preliminaries B/F				-
2.00	EARTHWORKS: EXCAVATION				
2.01	Excavate and remove topsoil average depth 150mm				
	and dispose the material off site	m ²	20		
2.02	Excavate, starting at strip level and not exceeding				
	300mm deep	m ³	3.5		
2.03	Excavate pits for column bases (1mx1m) starting from	3			
	ground level and not exceeding 1.0m deep	m ³	4		
2.04	Europeta atria formulation COOppus dose and COOppus				
2.04	Excavate strip foundation 600mm deep and 600mm wide for solar control room	m ³	4.5		
	wide for solar control room	""	4.5		
	Filling				
2.05	Filling to on the side of foundation blockwork				
	of selected excavated material deposited and				
	compacted in layers	m ³	2		
2.06	Ditto to make up levels below ground floor slab				
	of selected excavated material around the	3			
	borehole	m ³	3		
2.07	Ditto imported bonders are to rich of leterite				
2.07	Ditto imported hardcore materials of laterite ballstones , 200mm thick	m ²	11.5		
	ballstones , 200mm thick	""	11.5		
3.00	CONCRETE WORKS AND BLOCKWORKS				
3.01	Plain in-situ concrete mix (1:4:8-19mm aggregate)				
	as blinding to column bases	m ³	0.02		
2.02	Plain in-situ concrete mix (1:3:6 -19mm aggregate)				
3.02					
	in foundations poured against faces of excavation (strip foundation)	m ³	2.5		
	(strip roundation)	""	2.5		
3.03	Ditto: in 150mm thick ground floor slab and steps				
	for Solar control room	m ³	2		
3.04	Reinforced in-situ in column bases and columns in				
	foundations including reinforcement and				
	formwork (1:2:4;mix)	m ³	0.29		
	Formwork				
		2			
3.05	To edges of concrete floor slab, 150mm high.	m ²	2		
	Summary of Page B/d				

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,00P age 88 BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS Bill of Quantities

Item	Description	Unit	Qty	Unit Cost	Amount
No				(Le)	(Le)
	Summary of Page 2 B/F				
	Reinforced in-situ concrete 1:2:4 -12mm aggregates				
	including reinforcement and formwork				
3.06	Columns	m ³	7		
3.07	Beams (supporting 1st and 2nd suspended slabs)	m ³	4		
3.08	Suspended floor slab on where the first 10,000 litres				
	seats including reinforced concrete conopy	m ³	2.5		
3.09	Suspended floor slab where the second 10,000 litres				
	tank seats including reinforced canopy	m ³	2.5		
3.1	Provided 16mm dia. Reinforcing rods cut into				
	u-shape and bedded in one of the columss to be				
	used as ladder to the top of the tower	Lump Sum	1		
3.11	Scaffold: Erect and dismantle timber scaffolding				
	from 8m to 10m high tower construction	Lump sum	1		
	BLOCK WORK				
3.12	Precast sandcrete solid block 150mm thick in				
	cement mortar 1:6 for solar control room for both				
	the foundation and walls	m ²	48		
	FINISHING				
3.14	12mm thick cement and sand mix (1:4) plain face				
	rendered control room block walls internally				
	and externally	m ²	42		
3.15	VENTS ON CONTROL ROOM				
	Supply and fabricate vent opening on all thee sides				
	of control room of 500mm high by 1000mm wide				
	and fabricate grilled vents using 3/4" dia				
	rods wedded at 3" (76mm) interval vertically				
	and horizontally directions				
	Fix the grilled-end pipes 200mm long with the				
	5/8" dia rods inside in 1:2:4 - 12mm aggregate				
	reinforced concrete all round the edges of the				
	vents. Build a reinforced concrete canopy above the				
	door in the lintel stretching 600mm out to prevent				
	rainwater entering the door	No	3		
	Summary of Page 3 B/d				

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,00P agreed black milla tanks at Port Loko SLCS facility including distribution of water network into the facility & refurbishment of isolation units bill of Quantities

Item	Description	Unit	Qty	Unit Cost	Amount
No				(Le)	(Le)
	Summary of Page 3 B/F				-
	STEEL DOOR WITH LOCK				
3.16	Fabricate and fix steel door: Provide and fix steel				
	door 600mm x 2150 complete with frames, locks.				
	and ironmongery : Grilled 1/3 of the upper part and				
	the bottom 2/3 part should remain as steel plate				
	The upper part 1/3 of the door should be				
	grilled using 5/8" dia. reinforcing rods inside				
	50mm x 50mm RHS hollow pipe at 3" (76mm)				
	interval both vertical and horizontal directions				
	Build a reinforced concrete canopy above the				
	door in the lintel stretching 600mm out to prevent				
	rainwater entering the door	item	1	1,500,000	1,500,000.00
	PAINTING/DECORATION				
3.17	Prepare and apply one coat sealer and two coats				
	enamel paint to rendered surface of the of the				
	Control room internally and externally including				
	columns and ceiling of slabs	m ²	102	15,000	1,530,000.00
				·	
	SUPPLY AND INSTALL TWO (2) 10,000 L TANKS ON WATER TOWER				
3.18	Suply two mills tanks and mount them up on the				
	newly constructed reinforced concrete tower	No	2		
	COST OF WATER TOWER AND TWO 10,000 L MILLA TANKS				
	Contigency 5%				
	TOTAL COST OF WATER TOWER AND TWO 10,000 L MILLA TANKS				

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,000 BAGERS BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS

Item	Activity	Unit	Estimated	Unit Rate	Amount
No	Description		Quantity	(Le)	(Le)
_				ν - /	\ - <i>y</i>
4.00	WATER DISTRIBUTION NETWORK FROM BOREHOLE				
	STORAGE TANKS TO OTHER STORAGE TANKS AND THEN				
	DISTRIBUTION TO BATHROOMS, TOILETS, STAND TAPS IN				
	THE KITCHEN, AND LAUNDRY IN THE CORRECTIONAL				
	CENTRE				
	EXCAVATION AND TRENCHING:				
4.01	General clearance along pipeline	m	400		
4.02	Excavate trenches at least 600mm depth and with an				
	average width of 300mm to pass the pipes	m	400		
4.03	Backfill of trenches after pipes have been laid	m	400		
4.04	SUPPLY AND INSULLATION OF PIPES AND FITTINGS				
	Supply and instal all the require pipes and accessories into the				
	facility (Baths Toilets, Kitchen, Laundary).The pipes must be				
	high pressure pipes. approved by the supervising Engineer before				
	installation .Pressure test for pipes should be done in conformity				
	to engineering standard and approved by the Engineer				
4.05	Plumbing works (pipe and fitting assembly)	m	400		
4.06	Supply and Instal 1" x 2" galvanised reducer	Pcs	10		
4.07	Supply and Instal 1" PVC Tee	Pcs	10		
4.08	Supply and Instal 1" galvanised elbow	Pcs	12		
4.09	Supply and Instal 1" PVC elbow	Pcs	15		
4.10	Supply and Instal 1" galvanised nipple	Pcs	10		
4.12	Supply and apply PVC glue	Tin	6		
4.13	Supply and apply tread seal tape	Pkt	4		
4.14	Supply and Instal 3/4" galvanise tap head	Pcs	12		
4.15	Supply and Instal 1"galvanised elbow	Pcs	12		
4.16	Supply and Instal 1" PVC adaptor	Pcs	10		
4.17	Supply and Instal 1" gate valve	Pcs	8		
4.18	Supply and lay 25mm PE pipezsxs	m	300		
4.19	Supply and lay 50mm PE pipe	m	200		
4.2	Supply and install reducers PE 50mm x 25mm	Pcs	8		
4.21	Supply and install 25mm PE union	Pcs	10		
4.22	Supply and install 25mm PE control valve	Pcs	6		
4.23	Supply and install 25mm PE nipple	pcs	8		
4.24	Supply and install 50mm PE nipple	pcs	8		
4.25	Supply and install flex twin cables	roll	5		
	Water Distribution Network B/D				

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,00P ager 6s black milla tanks at Port Loko SLCS facility including distribution of water network into the facility & refurbishment of isolation units

No	Description		Quantity	(Le)	(Le)
	Water Distribution Network B/F				
4.25	Supply & Install 1"galvanised pipe 6m long for tap stands	length	6		
4.26	Supply and install 3/4" galvanised nipple	Pcs	8		
4.27	Supply and stall 3/4" galvanised socket	Pcs	10		
4.28	Supply and install 3/4" x1" reducer galvanized socket	Pcs	10		
4.29	Supply & Install 1"galvanised union	Pcs	8		
4.30	Supply & Install 2"galvanised pipe 6m long for inlet and				
	outlet pipes	length	6		
4.31	Supply & Install 2"galvanised pipe 6m long for outlet pipes	length	6		
4.32	Supply & Install 1"galvanised pipe 6m long for inlet baths	length	8		
4.33	Supply and install 2" coupling (galvanised socket)	Pcs	10		
4.34	Supply and install 2" PVC adaptor	pcs	8		
4.35	Supply and Install 2" galvanized elbow	Pcs	8		
4.36	Supply and Install 2" galvanized nipple	Pcs	8		
4.37	Supply and Install 2" galvanized gate valve	Pcs	8		
4.38	Supply and Install 1" gate for each tap stand	Pcs	6		
4.39	Construct valve chamber in block dept not exceeding 60 cm	No	5		
4.4	Supply and Fix locable valve cover (Mild steel) 400 x 500	No	5		
4.41	Supply and install conduit pipe	roll	1		
4.42	Excavate and an average depth of 600mm to remove				
	soil and with 300mm as trench to take pipes tp kitchen				
	bathrooms and toilets	m	200		
4.43	Inport and backfill trenches afterv pipes have been laid				
	and compact well				
4.44	Using Concrete, formwork and block construct a plateform				
	for the external stand pipe and in the kitchen	Item	2		
	COST FOR WATER DISTRIBUTION carried to summary				
	Contingency 5%				
	TOTAL COST FOR WATER DISTRIBUTION				-

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,000 BAFTER BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS

No	Description		Quantity	(Le)	(Le)
-	DEFLUDDICUMENT OF THE ISOLATION UNIT OF US				
5	REFURBISHMENT OF TWO ISOLATION UNIT CELLS				
5.01	Provide and install two squats to the new isolation				
	cells with all the accessories complete to both cells	No	2		
5.02	WIDENINING OF CELL VENTS AND GRILLED TO				
	IMPROVE ON VENTILATION				
	Widen the vents in the cell to 2 No 500mm x 1000mm				
	Fabricate new grilled vents using 3/4" diameter of High				
	tensile steel rods welded at 3" (76mm) interval vertical				
	and horizontal direction with mosquitoe wire mesh fixed				
	over the grilled vents as directed by the Engineer. The				
	grilled vents must be well enbedded into side using				
	1:2:4 mix -12mm aggregates reinforced concrete all round				
	the edge of the vents	No	4		
5.03	ALTER AND FIX ALL CELL DOORS TO GRILLED DOORS TO				
	IMPROVE ON VENTILATION				
	Remove all the metal doors leading to the cell.				
	Alter the door as follows: 2/3 of the bottom				
	part of each door should remain as steel plate				
	The upper part 1/3 of the door should be				
	grilled using 5/8" dia. reinforcing rods inside				
	50mm x 50mm RHS hollow pipe at 3" (76mm)				
	interval both vertical and horizontal directions				
	with mosquito wire mesh fixed over the grilled				
	areas ae directed by the Engineer or his rep .				
	Fix the grilled-end pipes 200mm long with the				
	5/8" dia rods inside in 1:2:4 - 12mm aggregate				
	reinforced concrete all round the edges of the	No	2		
	vent. Repair the door Locks				
5.04	PAINTING				
	Prepared one undercoat and one full coat oil pain in	m²	60		
	the two islolation cells	m m	60		
	COST ESTIMATES TO REFURBISH TWO ISOLATION UNITS				
	Contingency 5%				_
	35				
	TOTAL COST ESTIMATES TO REFURBISH TWO ISOLATION UNITS				-

REINFORCED CONCRETE WATER TOWER WITH TWO (2) 10,000 BEFFRS BLACK MILLA TANKS AT PORT LOKO SLCS FACILITY INCLUDING DISTRIBUTION OF WATER NETWORK INTO THE FACILITY & REFURBISHMENT OF ISOLATION UNITS

No	Description	Quantity	(Le)	(Le)
	SUMMARY			
Α	WATER TOWER AND TWO 10,000 L MILLA TANKS			
В	WATER DISTRIBUTION INTO THE FACILITY			
С	REFURBISHMENT OF ISOLATION UNIT CELLS			
	GRAND TOTAL WATER TOWER, WATER DISTRIBUTION INTO FACILITY AND REFURBISHMENT OF ISOLATION UNITS			