

Annex M-1

® Process Gauge - Stainless Steel

- Liquid-filled Case



Annex (M-2)

Standard first aid kit:

The contents of the first-aid kit listed should be adequate for small work sites, consisting of approximately two to three employees. When larger operations or multiple operations are being conducted at the same location, additional first-aid kits should be provided at the work site or additional quantities of supplies should be included in the first-aid kits:

1. Gauze pads (at least 4 x 4 inches).
2. Two large gauze pads (at least 8 x 10 inches).
3. Box adhesive bandages (band-aids).
4. One package gauze roller bandage at least 2 inches wide.
5. Two triangular bandages.
6. Wound cleaning agent such as sealed moistened towelettes.
7. Scissors.
8. At least one blanket.
9. Tweezers.
10. Adhesive tape.
11. Latex gloves.
12. Resuscitation equipment such as resuscitation bag, airway, or pocket mask.
13. Two elastic wraps.
14. Splint.
15. Directions for requesting emergency assistance.

Technical drawing of a vertical cylindrical component with a flange and a wavy base. The drawing includes dimensions for diameters (ØD1 , ØD2 , $\text{Ø}229 \pm 2.3$), radii ($R2$, $r \geq 17.2$), heights ($h1$, $H \geq 91.6$, 39.7 , 14.3 ± 2.2), and lengths ($L2 = 1460 \pm 20$, $L1 = 1295 \pm 20$). A note specifies a minimum thickness of 5 mm.

Marka altında kalan en az et kalınlığı/Min. guaranteed wall thickness below marking.