

Technical Specification

Sr	Description	Specifications		Quantity
3	UPS	Output	Output power capacity 600Watts / 1.0 kVA Max Configurable Power (Watts) 600Watts / 1.0 kVA Nominal Output Voltage 230V Efficiency at Full Load 84.0 % Output Frequency (sync to mains) 50/60 Hz +/-1 Hz Topology Line Interactive Waveform type Stepped approximation to a sinewave Output Connections (4) 3-pin 6A (Battery Backup) (2) 3-pin 6A (selector_surgetitle) Transfer Time 8ms typical : 12ms maximum	6 Units
		Input	Nominal Input Voltage 230V Input frequency 50/60 Hz +/- 3 Hz (auto sensing) Input Connections 3-pin 6A Cord Length 1.52meters Input voltage range for main operations 150 - 280 V Number of Power Cords 1 Efficiency at Full Load 84.0 %	

		Batteries & Runtime	Battery type Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof Typical recharge time 7.4hour(s) Expected Battery Life (years) 2 - 4 RBC Quantity 1 Extendable Run Time 1	
		Surge Protection and Filtering	Surge energy rating 680Joules	
		Environmental	Operating Environment 0 - 40 °C Operating Relative Humidity 0 - 95 % Operating Elevation 0-3000meters Storage Temperature -15 - 45 °C Storage Relative Humidity 0 - 95 % Storage Elevation 0-15000meters Audible noise at 1 meter from surface of unit 45.0dBA	
		Warranty	Standard warranty 2 years repair or replace	