


Heart of Amman project

Ras Alain social incubation offices


LEGEND & NOTES Walls to be demolished window to be removed and opened as door window to be removed and opened as door 18.75 __{.25}door to be closed **(D)** 0.00 Project Name : Heart of Amman project
Ras Alain social incubation offices GROUND FLOOR PLAN Plot umber 364 Drawing title: Ground floor demolition Scale: 1/100 Sheet No. A -0 0 1


Walls to be demolished





FIRST FLOOR PLAN

Scale: 1/100 Sheet No. A -0 0 2











LEGEND & NOTES

Project Name:

Heart of Amman project

Ras Alain social
incubation offices


Plot umber 364

Drawing title:

First floor furniture and annotation plan

Scale: 1/100 | Sheet | A -0 0 6

Reference	Floor	Skirting	Walls		
T01	60x60 porcelain tile, grey, matte	8cm porcelain tile, grey, matte	2 cm cement mortar with natural white paint		
T02	60x30 porcelain tile, grey, matte	į	60 x 30 grey porcelain		
T03	60x60 porcelain tile, grey, matte	8cm porcelain tile, grey, matte			



FIRST FLOOR PLAN



Project Name :

Heart of Amman project

Ras Alain social
incubation offices


Plot umber 364


Drawing title:

Ground floor tiling layout

Scale: 1/100 Sheet No. A -0 0 8

Reference	Description
	60cm x 60cm (18 w) european led light
	12 cm x12 cm (14 w) european led light
	10 cm x10 cm (7 w) white trimless led spot light
⊗ ⊣	Outdoor wall mounted led light. Height = +1.20 m







Project Name :

Heart of Amman project


Ras Alain social
incubation offices


Plot umber 364

Drawing title:


Ground floor lighting plan

Scale: 1/100 Sheet No. A -0 0 9





Project Name :



LEGEND & NOTES



Project Name : Heart of Amman project
Ras Alain social incubation offices


Plot umber 364

Drawing title:

Ground floor reflected ceiling plan

Scale: 1/100 Sheet No. A -0 10

Reference	Description
	60cm x 60cm (18 w) european led light
	12 cm x12 cm (14 w) european led light
#	10 cm x10 cm (7 w) white trimless led spot light
⊗ ⊣	Outdoor wall mounted led light. Height = +1.20 m





LEGEND & NOTES



Project Name:

Heart of Amman project


Ras Alain social
incubation offices

Plot umber 364


Drawing title:

First floor reflected ceiling plan

Scale: 1/100 Sheet No. A -011



Note: all compressors to be mounted on the upper roof





LEGEND & NOTES

Project Name :

Heart of Amman project
Ras Alain social
incubation offices

Plot umber 364


Drawing title:

Ground floor floor boxes and low current layout

Scale: 1/100 | Sheet | A -0 12

Floor box with universal 4 sockets Double sockets Ceiling mounted surveillance camera Access card control

Note: all compressors to be mounted on the upper roof



FIRST FLOOR PLAN



LEGEND & NOTES

Project Name : Heart of Amman project
Ras Alain social incubation offices

Plot umber 364


Drawing title:

First floor floor boxes and low current layout

Scale: 1/100 Sheet No. A -0 13

Floor box with universal 4 sockets Double sockets Ceiling mounted surveillance camera Access card control

Note: all compressors to be mounted on the upper roof



FIRST FLOOR PLAN



LEGEND & NOTES

Project Name : Heart of Amman project
Ras Alain social incubation offices


Plot umber 364


Drawing title:

First floor floor boxes and low current layout

Scale: 1/100 Sheet No. A -0 13







ELEC. SYMBOLS Fixture Schedule

LIGHTING SYSTEM

		LIGHTING SYSTEM
SYI	MBOL	DESCRIPTION
RL1	I	LED surface/recessed luminaire with CDP microprismatic cover. Luminaire luminous flux 4300 lm. luminaire efficiency 35.5 V, 1920
ERL1		Ditto as above but complete with emergency kit (1) hour duration.
RL2		LED surface/recessed luminaire with CDP microprismatic cover. Luminaire luminous flux 4100 lm, luminaire Ip40
ERL2	ЕМ	Ditto as above but complete with emergency kit (1) hour duration.
RL3		Ditto, As RI.2 But 40w
ERL3	□ем	Ditto as above but complete with emergency kit (1) hour duration.
RL4	(4)	Recessed LED ceiling luminaire Luminaire connected wattage 15.5 W 1795
ERL4	⊕EM	Ditto as above but complete with emergency kit (1) hour duration.
RL5	innnn innnn	Recessed LED28W downlight aluminium body with IP54
ERL5		Ditto as above but complete with emergency kit (1) hour duration.
RL6		Round LED downlight with highly specular aluminium reflector. Recessed downlight lP54
ERL6		Ditto as above but complete with emergency kit (1) hour duration.
RL7		LED surface/recessed luminaire with CDP microprismatic cover.
RL7	Ш	Luminaire luminous flux 4300 lm, luminaire efficiency 35.5 W, IP65
ERL7		Ditto as above but complete with emergency kit (i) hour duration.
WL1	4	Surface-mounted LED luminaires for ceiling and wall mounting 11 w - 1140
WL2	ð	LED wall luminaire with directed light. stainless steel Matt safety glass Luminaire connected wattage 15 W.Protection class IP65
WL3	2	Cubic LED wall luminaire for outdoor applications. 28W up and down led wall light, IP Rating IP65 Lamp Body Material: die—cast aluminum with glass diffuser
WL8	D	LED recessed huminaires for walls.Cast aluminium, stainless steel Safety glassand 20 W P 65 Luminaire made of aluminium alloy. aluminium and stainless steel Safety glass, white Reflector made of pure anodised aluminium
WL9	4	Wall Mounted Bulkhead Luminar With Wire Guard Galvani. Steel & Cast Aluminum Body 10W GLS Lamp.IP54.
SII	1	LES surface-mounted batten luminaire as single luminaire, 1154 mm. Surface direct-ceiling type 28w ,IP20
ESL1	EM	Ditto as above but complete with emergency kit
srs	ł	LED ceiling and wall luminaire for standard damp room applications. With opal polycarbonate diffuser, impact resistant.
ESL2	ЕМ	Ditto as above but complete with emergency kit (1) hour duration.
SL3		Surface direct—celling lighting luminaire mini square shape with opal wraparound glass diffuser led 15W IP44
SL4		Ceiling and wall luminaires 20W IP 65 Cast aluminium and Crystal glass, inside
ESL4	ем	Ditto as above but complete with emergency kit (1) hour duration.
SL5	F	Wall luminaires with indirect-direct light distribution. For 1 led tube lamp T8 18 Watt.
FLi	- À	LED floodlight for planar lighting and accent lighting. luminaire 50W Waterproof led floodlight wide beam Approval IP Rating:IP65
FL2	<u> </u>	LED floodlight for planar lighting and accent lighting. luminaire 75W Waterproof led floodlight wide beam Approval IP Rating:IP65
FL3	K	10W Waterproof LED Floodlight swimming pool with stainless steel made IP Rating: IP68 Operating Voltage: 24v-dc.
EM1	1 PAGE	8W Led emergency bulkhead offering maintained and non-maintained operation in one luminaire seeled to IP65
EM2		SW Led smergency bulkhead offering maintained and non-maintained operation in one luminaire sealed to IP40
ЕМЗ	8	WHILD EMERGENCY EXIT LIGHTING PIXTURE . THE PIXTURE SHOULD CONTAIN A BATTERY CHARGING DEVICE AND BATTERY UNIT
EM4	1	TO LIGHT LAMP FOR NOT LESS THAN 3 HOURS.IP40 DITTO (EMS) BUT DOUBLE FACE.
EM5		DITTO (EMS) BUT ONE FACE.
LP1	•	70-100W LED STREET LIGHT ON 7M STEEL POLE (SINGLE ARM).IP-86.
$\overline{}$		

ELEC. SYMBOLS Fixture Schedule

SOCKET SYSTEM

DESCRIPTION
ELEC POINT
BOILER CONTROL SWITCH WITH INDICATION LAMP .
LIGHTING SWITCH PANEL
PUSH BUTTON/CONTACTOR WITH PILOT LIGHTS.
16A DOUBLE POLE SWITCH WITH PILOT LAMP, FOR E.W.H
10A WALL/CEILING MOUNTED DOUBLE POLE SWITCH,
FOR EX. FAN WITH FAN SYMBOL
10A, ONE GANG -, TWO GANG, THREE GANG ONE WAY SWITCH.
10A, ONE GANG -, TWO GANG - TWO WAY SWITCH.
10A, INTERMEDIATE SWITCH.
2 COMPARTMENT FLOOR BOX WITH 13A SINGLE (SOCKET.,DATA) OUTLET
3 COMPARTMENT FLOOR BOX WITH 13A SINGLE
(SOCKET ,TEL.,DATA) OUTLET
Main Distribution Board.
MOTER CONTROL CENTER.
FINAL DISTRIBUTION BOARD (DB)
Main Telephone Terminal Box.
Sub Main Telephone Termenal Box
DATA CABINET
PRIVATE AUTOMATIC BRANCH EXCHANGE.
SERVER

ELEC. SYMBOLS Fixture Schedule

SOCKET SYSTEM

SYMBOL	DESCRIPTION
	3-POLE, 13Amp. SWITCHED SOCKET OUTLET,
	3-POLE, 16Amp. SWITCHED SOCKET OUTLET
۵	2- GANG, 3-POLE, 13Amp. SWITCHED SOCKET OUTLET,
A	3-POLE, 13Amp. SWITCHED SOCKET OUTLET, WATRE PROOF TYPE
	3-POLE, 16Amp. SWITCHED SOCKET OUTLET
	20A, DOUBLE POLE SWITCH WITH Indication Light. & CABLE OUTLET FIXED ABOVE FALSE CEILING FOR F.C.U.
4	3-POLE, 13Amp. SWITCHED SOCKET OUTLET, SPARK PROOF
古	2- GANG, 3-POLE, 13Amp. SWITCHED SOCKET OUTLET, H:250cm.
占	3-POLE, 13Amp. SWITCHED SOCKET OUTLET, -H:250cm.
	WIRELESS POINT H:250cm
0	Ceilling Power Elec. Point For Projector
*	TELEPHONE SOCKET OUTLET (RJ11).
•	T.V. AND SATELLITE SYSTEM SOCKET OUTLET
6	ELECTRIC WATER HEATER (SEE MECH. DWG. FOR DET. & SPECIFICATION).
Ā	SPN, ISOLATING SWITCH, IP-54 (FOR RATING REFER TO DRAWINGS).
H	TPN, ISOLATING SWITCH, IP-54 (FOR RATING REFER TO DRAWINGS).
C	RJ45 DATA SOCKET OUTLET
TH	THERMOSTAT BOX
EX.FAN	EXHAUST FAN OUTLET

- * ALL Switches to be fixed at hight 125cm from F.F.L. unless the switches beside beds at hight 70cm from F.F.L.
- * ALL Socket Outlets to be fixed at hight 35cm from F.F.L.
- unless the following outlet

 * Sockets in the Kitchen.

 Sockets for general use to be fixed at hight 110cm from F.F.L.

 Sockets for Frezer and refrigerator to be fixed at hight 150cm.



Project Name :

Heart of Amman project
Ras Alain social incubation offices


Plot umber 364

Drawing title:

ELEC. SYMBOLS

Scale: 1/100 Sheet Date: 8/2015 No. E - 01

LEGEND & NOTES



Project Name :


Drawing title:


Heart of Amman project
Ras Alain social
incubation offices

Plot umber 364

Ground floor lighting plan

Scale: 1/100 Sheet Date: 8/2015 No. E - 02







LEGEND & NOTES

Project Name :


Heart of Amman project
Ras Alain social
incubation offices

Plot umber 364

Drawing title:

GROUND floor SOCKETS PLAN

Scale: 1/100 Sheet No. E - 04



Project Name :

Heart of Amman project
Ras Alain social

Drawing title:


PLAN


incubation offices


Plot umber 364


First floor SOCKETS


Scale: 1/100 | Sheet | E - 05

















BREAKER	₹	130	LAIOI	\ 170	<u> </u>	احا	OAIL	JIZL	1		***	١ ١	
PANEL REF.		D.B.G				FEEDER SIZE CU/PVC CABLE 3x10mm2							
LOCATION GROUND					SUPPLY FROM MDB								
VOLTAGE FREQ	&	1PH	ASE,2	30V-50Hz		R/	ACE Tyf	YE WAY	32mm	PVC	CON	DUIT	
TYPE (OF	WIRE	COND	PHASE LOA	D TRIPI	NG	RA ⁻	E PHAS	SE_LOA	D COND	WIRE	TY	PE OF
LOAD)	SIZĘ mm)	WATT L	\dashv	Ĭ		W	/ATT L	SIZE	SIZE		_OAD
LIGHTING		1.5		750	1 10	A	10A	2	300		1.5		TING
LIGHTING		1.5		300	3 10	ΑΤ	15A	a 1	000		2.5	SOCI	KETS
SOCKETS	Ü	2.5] _ [1000	5 15	A		6 1	000		2.5	SOCI	KETS
SOCKETS		2.5	70	1000	7 15	٩I	15A	8 1	1000		2.5	SOCI	KETS
SOCKETS		2.5		600	9 15	A 115A	10 5	500		2.5	SOC	KETS	
SOCKETS KIT A/C		4.0		1500	11 20	DA] DA	1 20A 1 20A	12	1500		4.0	SOCK	ets kit
		4.0		1000	13 20			14 1	000		4.0	A/C	
A/C		4.0] '	1000	20	ΑĪ	10A	16	/	1	/	SPA	RE
SPARE		/	/	/	17 15	ΑŢ	20A	18	/	/	_	SPA	RE
PHASE	TOTA	AL\$W)		13450		Ī		·		•			
DISCR.	LIGHT	ΓING	SOCI	KETS	E,W,F	ł		FUTUR	E LOAD	TOTAL	PA CU	NEL RRENT	•
	WAT	Т	WATT		WA ⁻	WATT		WA	TTAW TTA			A	
CONNECTED LOAD WATT	135	50	1500	+ 6100	15	00		300	00	1345) 7	72	
DEM. FACT	66	%	100%	+ 40%	10	0%	7	40	%				
DEMAND LOAD WATT	80	00		3940	15	00		12	00	7400) 3	39	

BOARD SIZE 1-PN 18 WAY

1x63A

ISOLATOR

BREAKER

BREAKER	ISO	LATOF	1×63	A	BOARD	SIZE	1-PN	12	WA	Υ
PANEL REF.	D.B.	F			FEEDER	SIZE	CU/PVC 3x10mm	CAB 12	LE	
LOCATION	Т			SUPPLY FROM MDB						
VOLTAGE & 1PHASE,230V-50Hz					RACE WAY 32mm PVC CONDUIT					
TYPE OF LOAD	WIRE SIZE mm ²	COND SIZE mm	PHASE LOAD WATT	TRIPI	NG RATE		SE LOAD ATT	COND SIZE mm	WIRE SIZE	TYPE OF LOAD
LIGHTING	1.5		150	1 10	A 10A		350	111111	1.5	LIGHTING
SOCKETS	2.5		1100	3 15	A 15A	1	000		2.5	SOCKETS
SOCKETS	2.5		900	5 15	A 20A 6		500		4.0	E.W.H
A/C	4.0	20	1000	7 20	T / 119	1	000	20	4.0	A/C
A/C	4.0		1000	9 20	A 10A 10		/	/	/	SPARE
SPARE	/	/	/	1 15/	15A		/	/	/	SPARE
PHASE TOT	AL(W)		8000		-		·		,	

DISCR.	LIGHTING	SOCKETS	SOLAR HEATER	FUTURE LOAD	TOTAL	PANEL CURRENT
	WATT	WATT	WATT	WATT	WATT	Α
CONNECTED LOAD WATT	500	1100 + 1900	1500	3000	8000	62
DEM. FACT	66%	100% + 40%	100%	40%		
DEMAND LOAD WATT	300	1860	1500	1200	4860	26.40



Project Name :


Heart of Amman project
Ras Alain social
incubation offices


Plot umber 364


Drawing title:

ELEC.CALC.

Scale: 1/100 Sheet No. E -13









LEGEND & NOTES

Project Name :

Heart of Amman project


Ras Alain social
incubation offices


Plot umber 364

Drawing title:

DRAIN SYSTEM FOR First floor

Scale: 1/100 | Sheet | M - | |







LEGEND & NOTES

Project Name:

Heart of Amman project


Ras Alain social
incubation offices


Plot umber 364


Drawing title:

WATER SYSTEM FOR First floor

Scale: 1/100 | Sheet | M — () 4









Project Name :

Heart of Amman project


Ras Alain social
incubation offices


Plot umber 364


Drawing title:

A/C SYSTEM FOR Ground floor

Scale: 1/100 | Sheet | M — 0 = |









Project Name :

Heart of Amman project

Ras Alain social
incubation offices

Plot umber 364

Drawing title:

A/C SYSTEM FOR First floor

Scale: 1/100 | Sheet | M - | |