

REQUEST FOR QUOTATION (RFQ)

RFQ Reference: RFQ/UNDP/RESTORE/161300/040/2021 - Moveable GBV center in 40th Container	Date: 19 November 2021
--	------------------------

SECTION 1: REQUEST FOR QUOTATION (RFQ)

UNDP kindly requests your quotation for the provision of goods, works and/or services as detailed in Annex 1 of this RFQ.

This Request for Quotation comprises the following documents:

Section 1: This request letter

Section 2: RFQ Instructions and Data

Annex 1: Schedule of Requirements

Annex 2: Quotation Submission Form

Annex 3: Technical and Financial Offer

When preparing your quotation, please be guided by the RFQ Instructions and Data. Please note that quotations must be submitted using Annex 2: Quotation Submission Form and Annex 3 Technical and Financial Offer, by the method and by the date and time indicated in Section 2. It is your responsibility to ensure that your quotation is submitted on or before the deadline. Quotations received after the submission deadline, for whatever reason, will not be considered for evaluation.

Thank you and we look forward to receiving your quotations.

Issued by: Signature: Name: Martin Stephanus Kurnia Title: Head of Procurement Date: 19 November 2021

SECTION 2: RFQ INSTRUCTIONS AND DATA

Introduction	Bidders shall adhere to all the requirements of this RFQ, including any amendments made in writing by UNDP. This RFQ is conducted in accordance with the <u>UNDP Programme and Operations</u>
	Policies and Procedures (POPP) on Contracts and Procurement
	Any Bid submitted will be regarded as an offer by the Bidder and does not constitute or imply the acceptance of the Bid by UNDP. UNDP is under no obligation to award a contract to any Bidder as a result of this RFQ.
	UNDP reserves the right to cancel the procurement process at any stage without any liability of any kind for UNDP, upon notice to the bidders or publication of cancellation notice on UNDP website.
Deadline for the Submission of Quotation	Please refer to the etendering system with event ID: IDN10-0000011034 If any doubt exists as to the time zone in which the quotation should be submitted, refer to <u>http://www.timeanddate.com/worldclock/.</u>
	For eTendering submission - as indicated in eTendering system. Note that system time zone is in EST/EDT (New York) time zone.
Method of Submission	Quotations must be submitted as follows:
Submission	 ☑ E-tendering □ Dedicated Email Address
	Courier / Hand delivery
	□ Other Click or tap here to enter text.
	For eTendering method, click the link <u>https://etendering.partneragencies.org</u>
	•The Event ID fir etendering system: IDN10 - 0000011034
	Detailed instructions on how to submit, modify or cancel a bid in the eTendering system are provided in the eTendering system Bidder User Guide and Instructional videos available on this link: <u>https://www.undp.org/content/undp/en/home/procurement/business/resources-for-bidders</u>
Cost of preparation of quotation	UNDP shall not be responsible for any costs associated with a Supplier's preparation and submission of a quotation, regardless of the outcome or the manner of conducting the selection process.
Supplier Code of Conduct, Fraud,	All prospective suppliers must read the United Nations Supplier Code of Conduct and acknowledge that it provides the minimum standards expected of suppliers to the UN. The Code of Conduct, which includes principles on labour , human rights , environment and ethical conduct may be found at: <u>https://www.un.org/Depts/ptd/about-us/un-supplier-code-conduct</u>
Corruption,	Moreover, UNDP strictly enforces a policy of zero tolerance on proscribed practices, including fraud, corruption, collusion, unethical or unprofessional practices, and obstruction of UNDP vendors and requires all bidders/vendors to observe the highest standard of ethics during the procurement process and contract implementation. UNDP's Anti-Fraud Policy can be found at http://www.undp.org/content/undp/en/home/operations/accountability/audit/office_of_audit_andinvestigation.html#anti
Gifts and Hospitality	Bidders/vendors shall not offer gifts or hospitality of any kind to UNDP staff members including recreational trips to sporting or cultural events, theme parks or offers of holidays, transportation, or invitations to extravagant lunches, dinners or similar. In pursuance of this policy, UNDP: (a) Shall reject a bid if it determines that the selected bidder has engaged in any corrupt or fraudulent practices in competing for the contract in question; (b) Shall declare a vendor ineligible, either indefinitely or for a stated period, to be awarded a contract if at any time it determines that the vendor has engaged in any corrupt or fraudulent practices in competing for, or in executing a UNDP contract.
Conflict of Interest	UNDP requires every prospective Supplier to avoid and prevent conflicts of interest, by disclosing to UNDP if you, or any of your affiliates or personnel, were involved in the preparation of the requirements, design, specifications, cost estimates, and other information used in this RFQ. Bidders shall strictly avoid conflicts with other assignments or their own interests, and act without consideration for future work. Bidders found to have a conflict of interest shall be disqualified.

	Bidders must disclose in their Bid their knowledge of the following: a) If the owners, part-owners, officers, directors, controlling shareholders, of the bidding entity or key personnel who are family members of UNDP staff involved in the procurement functions and/or the Government of the country or any Implementing Partner receiving goods and/or services under this RFQ.
	The eligibility of Bidders that are wholly or partly owned by the Government shall be subject to UNDP's further evaluation and review of various factors such as being registered, operated and managed as an independent business entity, the extent of Government ownership/share, receipt of subsidies, mandate and access to information in relation to this RFQ, among others. Conditions that may lead to undue advantage against other Bidders may result in the eventual rejection of the Bid.
General	Any Purchase Order or contract that will be issued as a result of this RFQ shall be subject to the General
Conditions of	Conditions of Contract
Contract	Select the applicable GTC: General Terms and Conditions / Special Conditions for Contract.
	 ☐ <u>General Terms and Conditions for de minimis contracts (services only, less than \$50,000)</u> ⊠ <u>General Terms and Conditions for Works</u>
	Applicable Terms and Conditions and other provisions are available at <u>UNDP/How-we-buy</u>
Special Conditions of	\boxtimes Cancellation of PO/Contract if the delivery/completion is delayed by 10 days
Contract	□ Others [pls. specify]
Eligibility	A vendor who will be engaged by UNDP may not be suspended, debarred, or otherwise identified as ineligible by any UN Organization or the World Bank Group or any other international Organization. Vendors are therefore required to disclose to UNDP whether they are subject to any sanction or temporary suspension imposed by these organizations. Failure to do so may result in termination of any contract or PO subsequently issued to the vendor by UNDP.
	It is the Bidder's responsibility to ensure that its employees, joint venture members, sub-contractors, service providers, suppliers and/or their employees meet the eligibility requirements as established by UNDP.
	Bidders must have the legal capacity to enter a binding contract with UNDP and to deliver in the country, or through an authorized representative.
Currency of	Quotations shall be quoted in;
Quotation	☑ United States Dollars or
	☑ Local Currency : IDR (Mandatory for Local Bidders)
Joint	If the Bidder is a group of legal entities that will form or have formed a Joint Venture (JV), Consortium
Venture,	or Association for the Bid, they shall confirm in their Bid that : (i) they have designated one party to
Consortium	act as a lead entity, duly vested with authority to legally bind the members of the JV, Consortium or
or Association	Association jointly and severally, which shall be evidenced by a duly notarized Agreement among the legal entities, and submitted with the Bid; and (ii) if they are awarded the contract, the contract shall
Association	be entered into, by and between UNDP and the designated lead entity, who shall be acting for and on
	behalf of all the member entities comprising the joint venture, Consortium or Association.
	Refer to Clauses 19 – 24 under Solicitation policy for details on the applicable provisions on Joint
	Ventures, Consortium or Association.
Only one Bid	The Bidder (including the Lead Entity on behalf of the individual members of any Joint Venture, Consortium or Association) shall submit only one Bid, either in its own name or, if a joint venture, Consortium or Association, as the lead entity of such Joint Venture, Consortium or Association. Bids submitted by two (2) or more Bidders shall all be rejected if they are found to have any of the following:
	a) they have at least one controlling partner, director or shareholder in common; or b) any one of them receive or have received any direct or indirect subsidy from the other/s; or
	b) they have the same legal representative for purposes of this RFQ; or c) they have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about, or influence on the Bid of, another Bidder regarding this RFQ process;
	d) they are subcontractors to each other's Bid, or a subcontractor to one Bid also submits another Bid under its name as lead Bidder; or

	e) some key personnel proposed to be in the team of one Bidder participates in more than one Bid
	received for this RFQ process. This condition relating to the personnel, does not apply to
	subcontractors being included in more than one Bid.
Duties and taxes	Article II, Section 7, of the Convention on the Privileges and Immunities provides, inter alia, that the United Nations, including UNDP as a subsidiary organ of the General Assembly of the United Nations, is exempt from all direct taxes, except charges for public utility services, and is exempt from customs restrictions, duties, and charges of a similar nature in respect of articles imported or exported for its official use. All quotations shall be submitted net of any direct taxes and any other taxes and duties, unless otherwise specified below: All prices must:
	⊠ be exclusive of VAT and other applicable indirect taxes
Language of quotation	 English Others: Bahasa Indonesia for any legal certificate issued by the local government Including documentation including catalogues, instructions and operating manuals. Including documentation including catalogues, instructions and operating manuals.
Documents to	Bidders shall include the following documents in their quotation:
be submitted	Annex 2: Quotation Submission Form duly completed and signed
	Annex 3: Technical and Financial Offer duly completed and signed and in
	accordance with the Schedule of Requirements in Annex 1
	⊠ Company Profile.
	Registration certificate;
	☐ List and value of projects performed for the last 3 years plus client's contact details who may be contacted for further information on those contracts;
	⊠ List and value of ongoing Projects with UNDP and other national/multi-national organization with
	contact details of clients and current completion ratio of each ongoing project; Statement of satisfactory Performance (Certificates) from the top 2 (two) clients in terms of Contract
	value in similar field;
	\boxtimes Completed and signed CVs for the proposed key Personnel;
	\boxtimes Other list of relevant experiences.
Quotation	Quotations shall remain valid for 90 (Ninety) days days from the deadline for the Submission of
validity	Quotation.
period	
Price	No price variation due to escalation, inflation, fluctuation in exchange rates, or any other market factors
variation	shall be accepted at any time during the validity of the quotation after the quotation has been received.
Partial Quotes	⊠ Not permitted
Quotes	Permitted Insert conditions for partial quotes and ensure that the requirements are properly listed
Alternative	in lots to allow partial quotes
Quotes	 ☑ Not permitted □ Permitted
	If permitted If permitted, an alternative quote may be submitted only if a conforming quote to the RFQ requirements is submitted. Where the conditions for its acceptance are met, or justifications are clearly established, Click or tap here to enter text. reserves the right to award a contract based on an alternative quote. If multiple/alternative quotes are being submitted, they must be clearly marked as "Main Quote" and "Alternative Quote"
Payment	□ 100% within 30 days after receipt of goods, works and/or services and submission of payment
Terms	documentation. ⊠ Other (Please refer to the payment schedule mentioned in the TOR)
Conditions	⊠ Passing Inspection [specify method, if possible]
for Release of	\boxtimes Complete Installation
Payment	⊠ Passing all Testing [specify standard, if possible]
	Completion of Training on Operation and Maintenance [specify no. of trainees, and location of training, if possible
	Written Acceptance of Goods, Services and Works, based on full compliance with RFQ
	requirements
	Others upon acceptance and approval of each deliverable

~ · · ·				
Contact	E-mail address: sri.hastutiningsih@undp.org and Yusef.millah@undp.org			
Person for				
corresponden	Attention: Quotations shall not be submitted to this address but to the address for quotation			
ce,	submission above. Otherwise, offer shall be disqualified.			
notifications	Any delay in UNDP's response shall be not used as a reason for extending the deadline for			
and	submission, unless UNDP determines that such an extension is necessary and communicates a			
clarifications	new deadline to the Proposers.			
Clarifications	Requests for clarification from bidders will not be accepted any later than 2 (two) days before the submission deadline. Responses to request for clarification will be communicated by etendering system and UNDP Global Website by 2 (two) days before the deadline.			
Evaluation	⊠The Contract or Purchase Order will be awarded to the lowest price substantially compliant offer			
method	□ Other Click or tap here to enter text.			
Evaluation	☐ Full compliance with all requirements as specified in Annex 1			
criteria	⊠Full acceptance of the General Conditions of Contract			
	Comprehensiveness of after-sales services			
	1			
	Earliest Delivery /shortest lead time			
	Others Click or tap here to enter text.			
Right not to	UNDP is not bound to accept any quotation, nor award a contract or Purchase Order			
accept any				
quotation	At the time of award of Contract or Purchase Order, UNDP reserves the right to vary (increase or			
Right to vary requirement	decrease) the quantity of services and/or goods, by up to a maximum twenty-five per cent (25%) of			
at time of	the total offer, without any change in the unit price or other terms and conditions.			
award	the total offer, whole any change in the unit price of other terms and conditions.			
Type of	Purchase Order			
Contract to				
be awarded	Contract Face Sheet (Goods and or Services) (this template is also utilised for Long-Term			
	Agreement) and if an LTA will be signed, specify the document that will trigger the call-off. E.g., PO, etc.)			
	Contract for Works			
Farmer 4	Other Type/s of Contract [pls. specify]			
Expected	20 December 2021			
date for contract				
award.				
Publication	UNDP will publish the contract awards valued at USD 100,000 and more on the websites of the CO			
of Contract	and the corporate UNDP Web site.			
Award				
Policies and	This RFQ is conducted in accordance with UNDP Programme and Operations Policies and Procedures			
procedures	The set of the conductor in accordance with or of the rough and operations roughes and roughd and			
UNGM	Any Contract resulting from this RFQ exercise will be subject to the supplier being registered at the			
registration	appropriate level on the United Nations Global Marketplace (UNGM) website at <u>www.ungm.org</u> .			
-9	The Bidder may still submit a quotation even if not registered with the UNGM, however, if the Bidder is selected for Contract award, the Bidder must register on the UNGM prior to contract signature.			

Other	Site visit to pilot location (DSUD Congkarong)
Other Information	Site visit to pilot location (RSUD Cengkareng) Day/Date: Thursday, 25 November 2021
mormation	Time: $10.00 - 12.00$ Jakarta's time
	Place: RSUD Cengkareng
	JI. Kamal Raya Bumi Cengkareng Indah No. 1 Cengkareng Timur Jakarta Barat 11730
	Ji. Kamai Kaya Dumi Cengkareng muan 100. 1 Cengkareng Timui Jakarta Darat 11750
	The UNDP focal point for this site visit are:
	Atikkumala Dewi/ Nihandini Santi
	Email: <u>atik.dewi@undp.org</u> / <u>nihandini.santi@undp.org</u>
	Bid Conference through zoom meeting
	Day/Date: Friday, 26 November 2021
	Time: start at 10.00 AM Jakarta time (GMT +7)
	Zoom Link:
	https://undp.zoom.us/j/88654906580?pwd=ajZGZ01DVGIwVWR3c0dXTm94WWJ3dz09
	Meeting ID: 886 5490 6580
	Password: 357925
	Detailed Terms of Reference as well as other requirements are listed in the RFQ available on UNDP ATLAS e-Tendering system" (<u>https://etendering.partneragencies.org</u>) as written in the method of submission.
	If you have not registered in the system before, you can register by logging in using: Username: event.guest Password: why2change
	The step by step instructions for registration of bidders and quotation submission through the UNDP ATLAS e-Tendering system is available in the attached "Instructions Manual for the Bidders". Should you require any training on the UNDP ATLAS e-Tendering system or face any difficulties when registering your company or submitting your quotation, please send an email to sri.hastutiningsih@undp.org.
	Please note that ATLAS has following minimum requirements for password:1. Minimum length of 8 characters;2. At least one capital letter; and3. At least one number.
	New proposer registering for the first time, the system will not accept any password that does not meet the above requirement, and thus registration cannot be completed.
	For existing vendor whose current password does not meet the abovementioned password requirements, the system will prompt you to change your password upon signing in. Please change your password in accordance with the abovementioned password requirements to be able to login to the system.
	The user guide and video are available to you in the UNDP public website in this link: <u>https://www.undp.org/content/undp/en/home/procurement/business/resources-for-bidders.html</u>
	You are advised to use Internet Explorer (Version 10 or above) to avoid any incompatibility issues with the e-tendering system.

ANNEX I: SCHEDULE OF REQUIREMENTS

1. EXECUTIVE SUMMARY

UNDP is committed to support the Government of Indonesia (GoI) to improve Gender Based Violence (GBV) service providers for handling GBV cases through strengthening integrated hospital-based services. This commitment has been implemented since 2018 through establishing a pilot of the PPT Bunga Tanjung at Tarakan Hospital which has adopted the concept of an integrated GBV cases handling of "Sun Flower" in South Korea. Following up on this commitment, UNDP plans to re-strengthen the integrated GBV cases handling service in hospital through developing a prototype of "moveable integrated service center" for GBV victims piloted at RSUD Cengkareng in Jakarta. This prototype aims to unifying several services-provided by different institutions and providing them under a single roof to ensure all rights of GBV victims and survivors accommodated.

Objective

- 1. Construct the Movable GBV facility with 3i basic principles, including integrated, inclusive, and independent in a 40 ft container, fully equipped to provide integrated services to GBV victims in affected populations in RSUD in Jakarta.
- 2. Develop Detail Engineering Design (2D and 3D) of the Movable (Pusat Pelayanan Terpadu/ one stop center for GBV victims) prototype design in consultation with UNDP through at least 3 (three) consultation meetings.

Location

The facility will be constructed in RSUD Cengkareng in DKI Jakarta with confirmed space that can accommodate the 40 ft container and its specification needs

Scope of work - Mandatory Requirements (100%) - without meeting these requirements, bidder will NOT be eligible to participate

- 1. The selected company is required to construct the Movable GBV facility and its equipments with the capacity in accordance provided specification. Prior construction, the selected company shall develop Detail Engineering Design (2D and 3D) of the Movable PPT prototype design, including blueprint of plumbing and electric in consultation with UNDP through at least 3 (three) consultation meetings. The construction of the Movable PPT can only be started after approval by UNDP on the final 2D and 3D of the Detail Engineering Design and must be completed by December 2021 at the latest.
- 2. The selected company must provide and implement the construction conforming with the Indonesian and International standard, including:
 - Quality management system (QMS) ISO 9001, Occupational Health and Safety Assessment Series (OHSAS) ISO 45001, Environmental Management System (EMS) ISO 14001.
- 3. The selected company must prepare a detailed budget and responsible for the installation, setting up and commissioning for the below utility systems and ensure they are fully functional **with the following benchmarks**:

A. Clean water using Up feed system

Connecting host hospital has a system to pump water from the water reservoir below to be connected to the container. Clean water pipes must use superior materials with SNI certification.

B. Dirty water network using the Single Stack System

All the sanitary appliances in a single stack. In this system, the main stack itself serves as the vent. It has simple design procedure, which relates hydraulic discharge in the stack to the pipe diameter for permissible suction inside stack. The drain pipe must use superior material. Superior material PVC with SNI certification.

C. Waste distribution system - using Junk Shaft Network

It is a vertical waste distribution system using vertical waste channels from container to the garbage disposal of the hospital and then transported by the cleaning staff.

D. Electrical system

Connecting the main electricity supply from the on-grid solar panel of 4400 watts to hospital PLN system using ON GRID Solar Panel with 4400 watt capacity. Ensure that EXIM meter is installed, set up and commissioned if not available. PLN electricity consumption is used when electricity from On Grid Solar Panel exceeds the quota or when the weather is bad so it is distributed to PLN. The cable network that will be used is through an underground cable network.

Important notes: One day site visit to the location will be arranged by UNDP team for all interested vendors during the solicatiation period, **BEFORE** the bid conference. All technical questions pertaining to location, logistics for the purpose of shipping and installment of the container at hospital **shall be probed** in bid conference.

4. Selected company should assure 3 month service warranty for container commissioning.

Qualification

The Contractor will work under the guidance and supervision of UNDP project management team.

IMPORTANT NOTE: Bidders that do not comply with the minimum requirements listed below may be directly disqualified.

Company requirements

- Contractor with legal business certificate to operate in Indonesia.
- Contractor with classification for building construction work who has at least 2 times of experience in constructing and renovating infrastructure over the past 7 years.
- Contractor with healthy financial resources to deliver outputs as per payment terms based on project budget with quality assurance and control as per requirements stipulated in the RfQ
- Contractor with skilled personnel and self-sufficient human resources to deliver outputs with quality assurance and control as per requirements stipulated in the RfQ, including architectural consultation services
- Contractor with self-sufficient technical and operational capacities, including equiptment/ tools, spare part, service and repairs

IMPORTANT NOTE: The vendor is expected to submit a brief description of relevant past assignments with contacts for reference check.

- The offeror is not under procurement prohibition by the United Nations, including but not limited to prohibitions derived from the Compendium of United Nations Security Council Sanctions Lists;
- The offeror has not been suspended, debarred, sanctioned or otherwise identified as ineligible by any UN Organization or any other international Organization.
- The offeror has no conflict of interest in undertaking this assignment; it does not employ, or anticipate employing, any person(s) who is, or has been a UN staff member within the last year, if said UN staff member has or had prior professional dealings with the firm in his/her capacity as UN staff member within the last three years of service with the UN
- The offeror has not declared bankruptcy, are not involved in bankruptcy or receivership proceedings, and there is no judgment or pending legal action against them that could impair their operations in the foreseeable future; and undertake not to engage in proscribed practices, including but not limited to corruption, fraud, coercion, collusion, obstruction, or any other unethical practice, with the UN or any other party, and to conduct business in a manner that averts any financial, operational, reputational or other undue risk to the UN and we embrace the principles of the United Nations Supplier Code of Conduct and adhere to the principles of the United Nations Global Compact.

Payment Terms

Deliverable/Outputs	Estimated Due date	Condition of Payment	Percentage of Payment
1 st Deliverable – upon completion on:	December 2021	Upon approval from	60%
1) Detail Engineering Design (2D and 3D) of 40 ft		GBV project unit	
Container;			
 Detail design of plumbing system for clean water and waste water in blueprint; 			
3) Detail design of electrical system in blueprint; and			
4) Detailed budget for cosntruction, installation and			
commissioning of 40 ft Container for Purchase Order			
(PO).			
2^{nd} Deliverable – upon completion on a report of	January 2022	Upon approval from	30%
installation, (including installation of on grid solar and		GBV project unit	
EXIM meter), shipping, setting up and commissioning			
of 3i Moveable GBV Sevice Center, ensuring that the			
container is fully functional and conforms with			
electrical, plumbing, clean water, waste water and			
drainage system of host hospital.			
3 rd Deliverable- upon completion of 3 month service	March 2022	Upon approval from	10 %
warranty of the 40 ft GBV Container.		host hospital of	

	container commissioning and completion of a 3 month service warranty	
--	---	--

Implementation Period

The period of deliverable scope of work for constructing Movable GBV Facility is 1 month (December 2021 – January 2022).

2. SPECIFICATION OF MOVABLE GBV FACILITY

Dimensions: 1 x 40ft container. Easy access to medical examination room and counselling room shall be provided via a corridor/ hallway.

The Moveable GBV center shall be designed to have the following rooms:

- 1. Waiting room equipped with folding furniture and enclosed with sliding door to ensure confidentiality of other rooms
- 2. Medical Examination room
- 3. Multi functional room for recovery and counselling multi-functional room to accommodate different needs for recovery and counselling
- 4. Corridor

Requirements for the container:

- 1. Elevated sunroof on entire container
- 2. Container to be coated with medical floors and walls
- 3. Air conditioning
- 4. Ventilation
- 5. Lighting system inside the container
- 6. Equipped with clean water system conform to Indonesia's health and safety standards
- 7. Equipped with drainage system for wastewater conform to Indonesia's health and safety standards
- 8. Sliding doors should be tinted (to ensure privacy), coated for anti corrosion and tropical climate resilient, with minimum width 90 cm to allow access for wheelchair,

On Grid Solar power:

Solar Panel Capacity: 4 kWp/ 4400 Watt

Type: Monocrystalline

Conform to the requirement of the installation to the hospital power grid and compatible to the host's EXIM meter ✓Frameless module

✓High Durability Solar Panel

✓ Solar Cell Warranty : 25 years

✓Inverter Warranty : 5 years

✓Instalation Warranty : 1 year

A. Clean Water Tank and Waste Water System

- 1. Ensure proper system/ connection of clean water system and waste water system with the host hospital's clean water and waste-water system.
- 2. 400 liter water tank
- 3. ¹/₂ hp shallow well water pump automatic water pump for clean water system compatible with the source of clarn water system of the host hospital
- 4. 22.75 liter pressure tank
- 5. There must be separately pipe installations for hot and cold water;
- 6. There must be from 30-liter capacity, electrical water heater;
- 7. There must be level gauge and feeding discharging valves on the both tanks;
- 8. Stainless steel sink (with foot activated faucet, no need to touch for water);

B. Electric water heater:

Electrical water heater, size 30 L, 1.5 kW electrical resistance, wall mounted, 50mm foam insulated, of high quality, including wall brackets, price shall include all required fittings, accessories, safety valve, angle valves, flexible hoses, etc. as per engineer's instructions and approval.

C. Pipes:

- 1. Separate pipe installations for cold and hot water.
- 2. The pipes and fitting used for cold water shall be UPVC, and hot water shall be PPR. Both of pipes and fitting shall conform to SNI.
- 3. All change in direction in drainage pipes shall be gradual and not abrupt.
- 4. Installation of plumbing and fitting will follow the approved drawing/ blueprint
- 5. All pipes shall be plain ended lengths for seal ring connection to all fittings.
- 6. All pipe jointing and supporting shall be made as recommended by the pipe's manufacturer.
- 7. All pipes and fittings including adapters, couplings and connectors shall be marked with the manufacturer name, SNI. number and diameter.
- 8. All exposed pipes shall be provided with suitable paint for climate resilient for tropical climate

D. Sanitary fixtures:

- 1. All plumbing fixtures shall comply with particular and general specifications and shall be provided with all necessary builders' work material and accessories to enable support and connection.
- 2. All items of sanitary ware shall be obtained from a single manufacturer and shall be of 1st class quality without any blemishes, marks, grazing of glaze, chips or the like whatsoever.
- 3. Install plumbing fixtures and fittings in accordance with the manufacturer's recommendations. Refer to architectural drawings for exact location of fixtures and fittings.
- 4. All colors for plumbing fixtures, fittings, are subject to the approval of the Engineer.

E. Split Type AC

- 1. There must be 3 pieces. 12.000 btu heating and cooling capacity split type AC on each unit.
- 2. They must have easily changeable filters
- 3. Copper hose installations for high efficiency
- 4. All AC units must be min. A+ invertor type
- 5. Remote controller
- 6. There must be drainage system for condensed waters and these drainage systems should be cover with channel.
- 7. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up.
- 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation.
- 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed.
- 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor.
- 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes.
- 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation.
- 13. The heating mode operation temperature should be between $(-15\sim24)$ °C.
- 14. The cooling mode operation temperature should be between $(-10 \sim 46)$ °C.
- 15. Units should have EER up to 3.8 and a COP up to 4.12.
- 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit.
- 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation.
- 18. The outdoor fan should be driven by DC Inverter motor.
- 19. Unit should have a Cross Flow fan for uniform distribution.

- 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. **Specs:**
 - 22.10.1RPM: 925 1085
 - 22.10.2Capacity (CFM): as shown on the drawings.
 - 22.10.3Motor Rating: 240V / 50Hz
 - 22.10.4Motor W: Low 31.8 High 38.8
 - 22.10.5Noise Level (dB): < 40

F. Inside Lighting

- 1. All Lights should be heavy duty and decorative LED lighted to use long-life.
- 2. Lights must be Long durability and energy saving option
- 3. There must be Emergency Light option for each room
- 4. There should be sensor when there is no electricity some of lights should be automatically turned on.

G. Storage Areas

- 1. All cabinets locks must be corrosion protected
- 2. Storage cabinets should be high isolated to protect the powder and water leakage

H. Painting

- 1. Min. 3 times epoxy primary coated (corrosion protected);
- 2. All Steel parts shall be Sandblasted to be protected from the corrosion;
- 3. Three times final coating with Epoxy paint.
- 4. Medical examination will be painted in white hue color (TBC), ensuring aesthetically appealing with furniture design
- 5. Remaining rooms will be painted in soft pink hue color (TBC), ensuring aesthetically appealing with furniture design

I. Electrical Panels and Equipment's

- 1. All electrical cables are fire protected and shielded.
- 2. All electrical and data cables must be jointless,
- 3. Electrical Panels are IP65 protected. Water and Powder protected.
- 4. PLC (Programmable Logic Controller) controlled in the Electrical Panels.
- 5. There should be Phase Control Relay to protect the wrong connection in the Electrical Panels.
- 6. There should be Thermic Magnetic Switch to protect the High Voltage.
- 7. All electronic components should be certified
- 8. There must be external electric connection socket. This socket must be min. IP67 Protection level.
- 9. There must be 10-meter extension cable with protection covers
- 10. Rough electrical uses UL listed metal clad 12/2 solid copper wires and galvanized metal boxes.
- 11. Universal duplex electrical outlets. Will accept all electrical cords plug-in.
- 12. Outlets and switches are all flush mounted in the walls to assist with infection control.
- 13. GFCI duplex outlet or circuit if an outlet is located within 6 feet of a water source.
- 14. Available in 230V, 50/60 Hz options.

J. Walls and Ceilings

- 1. Covered with a 0.55mm full color thickness non-FRP washable surface that has been pre-laminated to a 3/8" / 1.0 cm
- 2. OSB board
- 3. OSB board has been treated with an anti-termite mineral.
- 4. Walls and ceiling are secured using both Liquid Nail Heavy Duty construction adhesive and 1 ¹/₄" dry wall screws.

K. Internal Floors

- 1. All floor surfaces must be made by heavy duty steel chassis. There must be reinforcement bars and inside equipment fixing points;
- 2. All floor surfaces must be cover with min18 mm marine type plywood;
- 3. There must be min. 50 mm XPS isolation material for all floor surfaces;
- 4. All floor surfaces are coated with 2 mm Anti-static, Anti-slip safe, washable hospital vinyl antibacterial PVC;
- 5. There must be min. 7 cm oval skirting all around the inside floor corners (anti-bacterial surface);
- 6. Aluminum or stainless-steel extruded covers for operational gaps;
- 7. All floors should be high isolated to protect the powder and water leakages;

- 8. Floors should be washable and cleanable.
- 9. Armstrong Medley Medical Grade seamless vinyl flooring with flash coving.

L. Sound proofed and climate resilient wall

- All walls should be sound proofed and climate resilient (tropical climate).
 All walls should be high isolated to protect the powder and water leakages.
- 3. Walls should be cleanable.

IMPORTANT:

The UNDP Logo, Hospital Logo and the Logo of the Department of Health of DKI Jakarta Province shall be painted on the front wall on the entrance door of the hospital - to be confirmed upon consultation meetings with UNDP.



Attachment to Annex I: SCHEDULE OF REQUIREMENTS

Technical Specifications for Goods:





Item No	Description	UoM	Qty	Unit Price	Total Price
1.	Services for producing detailed Engineering Design (2D and 3D) of the Movable PPT prototype, including blueprint for plumbing and blueprint for electrical system in consultation with UNDP (3 meetings)	Package	1		
	Services for construction, installation, setting up and commissioning of 3i Moveable GBV Sevice Center:	Package	1		
	Dimensions : 1 x 40ft container. Easy access to medical examination room and counselling room shall be provided via a corridor/ hallway.				
	The Moveable GBV center shall be designed to have				
	 the following rooms: 1. Waiting room – equipped with folding furniture and enclosed with sliding door to ensure confidentiality of other rooms 2. Medical Examination room 3. Multi functional room for recovery and counselling - multi-functional room to accommodate different needs for recovery and counselling 4. Corridor 				
	Requirements for the container:				
	 Elevated sunroof on entire container Container to be coated with medical floors and walls Air conditioning Ventilation Lighting system inside the container Equipped with clean water system conform to Indonesia's health and safety standards Equipped with drainage system for wastewater conform to Indonesia's health and safety standards Sliding doors should be tinted (to ensure privacy), coated for anti corrosion and tropical climate resilient, with minimum width 90 cm to allow access for wheelchair On Grid Solar power: Solar Panel Capacity: 4 kWp/ 4400 Watt 				
	Solar Panel Capacity: 4 kWp/ 4400 Watt Type: Monocrystalline Conform to the requirement of the installation to the hospital power grid and compatible to the host's EXIM meter ✓Frameless module				
	 ✓High Durability Solar Panel ✓Solar Cell Warranty : 25 years ✓Inverter Warranty : 5 years ✓Instalation Warranty : 1 year 				

А.	Clean Water Tank and Waste Water System			
	1. Ensure proper system/ connection of clean			
	water system and waste water system with the			
	host hospital's clean water and waste-water			
	system.			
	2. 400 liter water tank			
	3. ¹ / ₂ hp shallow well water pump - automatic			
	water pump for clean water system			
	4. 22.75 liter pressure tank			
	5. There must be separately pipe installations for			
	hot and cold water;			
	6. There must be from 30-liter capacity, electrical water heater;			
	7. There must level gauge and feeding discharging			
	valves on the both tanks;			
	8. Stainless steel sink (with foot activated faucet,			
	no need to touch for water);			
-				
В.	Electric water heater:			
	Electrical water heater, size 30 L, 1.5 kW electrical			
	resistance, wall mounted, 50mm foam insulated, of			
	high quality, including wall brackets, price shall			
	include all required fittings, accessories, safety			
	valve, angle valves, flexible hoses, etc. as per			
	engineer's instructions and approval.			
C.	Pipes:			
	1. Separate pipe installations for cold and hot			
	water.			
	2. The pipes and fitting used for cold water shall			
	be UPVC, and hot water shall be PPR. Both of			
	pipes and fitting shall conform to SNI.			
	3. All change in direction in drainage pipes shall			
	be gradual and not abrupt.			
	4. Installation of plumbing and fitting will follow			
	the approved drawing/ blueprint			
	5. All pipes shall be plain ended lengths for seal			
	ring connection to all fittings.			
	6. All pipe jointing and supporting shall be made			
	as recommended by the pipe's manufacturer.			
	7. All pipes and fittings including adapters,			
	couplings and connectors shall be marked with			
	the manufacturer name, SNI. number and			
	diameter.			
	8. All exposed pipes shall be provided with			
	suitable paint for climate resilient for tropical			
	climate			
	ennace			
D.	Sanitary fixtures:			
	1. All plumbing fixtures shall comply with			
	particular and general specifications and shall be			
	provided with all necessary builders' work			
	material and accessories to enable support and			
	connection.			
,	2. All items of sanitary ware shall be obtained from			
-	a single manufacturer and shall be of 1st class			
	quality without any blemishes, marks, grazing of			
,	glaze, chips or the like whatsoever.			
-	3. Install plumbing fixtures and fittings in			
	accordance with the manufacturer's			
	recommendations. Refer to architectural			

 4. All colors for plumbing fixtures, fittings, are subject to the approval of the Engineer. E. Split Type AC There muss the 3 pieces. 12,000 btu heating and cooling capacity split type AC on each unit. They muss have easily changeable filters Copper these installations for high efficiency All AC units muss the min. A invertor type Remote controller There muss the drainage system for condensed waters and these drainage system should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, aris cooled outdoor unit, designed for roof, slab or floor mounting. Commot be all factory within the unit colosurs shall be all factory within, the unit colosurs shall be all factory within the unit colosurs that be all factory withing, piping, Consisting of DC compressors. DC fan motor, condensers, evaporator fams, holding charge of R410 Refrigerant und temperature control, filters and special features required prior to field start up. Outdoor min closing shall be constructed of galvanized steel; compressors comparisons (Page 100, Page 100, Pag		drawings for exact location of fixtures and	
 subject to the approval of the Engineer. E. Split Type AC There must be 3 pieces. 12,000 but heating and cooling capacity split type AC on each unit. They must have easily changeable filters Copper hose installations for high efficiency All AC units must be min. A invertor type Remote controller There must be drainage system for condensed waters and these drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, cach one complete piece, arit cooled outdoor units, cach one complete piece, arit cooled outdoor units, contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors. DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special fastures required prior to field start up. Outdoor unit cabinet shall be constructed of galvanized steel; compressors compartment shall be isolated to assarre quice operation. Condenser rans shall be there drive, A Pole, DC Rotary Inverser motor for all units except the unit with cooling capacity 5 KV which is Scroll DC (inverter motor. Condenser coil shall be constructed of aluminium fins mechanically bonded to internally enhance same scoper tubes. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. The between (-15-24) °C. The cooling mode operation temperature should be between (-15-24) °C. Outdoor unit should be all the air cooled aplit by system. The outdoor unit should be air cooled aplit system. The cooling mode operation temperature should be between (-10 - 46) °C. The cooling mode operation temperature should be between (-16 - 46) °C. The cooling mode operation temperature should be between (-10 - 46) °C. The outdoor unit should be driven by		•	
 E. Split Type AC There must be 3 pieces. 12.000 but heating and cooling capacity split type AC on each unit. They must have easily changeable filters Copper bose installations for high efficiency All AC units must be min. A invertor type Remote controller There must be drainage system for condensed waters and these drainage system should be cover with channel. There must be drainage system for condensed waters and these drainage system should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping. Consisting of DC compressors. DC fam motor, condensers, evaporator finas, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. Outdoor unit abinet shall be constructed of galvanized steel; compressor compartuent shall be isolated to assure quier operation. Condenser fams shall be direct drive Propeller type, and motors shall be totally vendoed. Contarger motors shall be callify enclosed. Contarger motors shall be callify enclosed. Condenser fams shall be constructed of aluminum fins mechanically bonded to internally enhance scameles copper tubes. Univ with no need low ambient control kit as the operation in the unit should be a low ambient operation. The bating mode operation temperature should be between (10 - 46) °C. Univ sith dual have ERR up to 3.8 and a COP up to 4.12. O- Operation should be driven by DC linverter motor. Univ sith dual have ERR up to 3.8 and a COP up to 4.12. Ouries should be accored split system. Outdoor scins should be there on the ground/roof op installation. 	4		
 There must be 3 pieces. 12.000 bm heating and cooling capacity split type AC on each unit. They must have easily changeable filters Copper bose installations for high efficiency All AC units must be min. A+ invertor type Remote controller There must be drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab of floor mounting, Contained within the unit enclosure shall be all factory wing, piping. Consisting of DC compressors, DC fam motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required priorito field start up. Outdoor unit cabinet shall be constructed of galvanized stech (compressor compartment shall be isolated to assure quite operation. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. Condenser coil shall be constructed of aluminum fins mechanically bonded to intermally enhance scameloss copper tubes. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. The heating mode operation temperature should be between (-15-24) °C. Into the one of ward and by a site of 43404 have ER up to 3.8 and a COP up to 4.12. Ourdoor unit should be air cooled split system. Outdoor suits bey adopting plastic case. Plastic fan and Mulit positions airflow volume swith decarcases noise to 4340B(A)		subject to the approval of the Engineer.	
 There must be 3 pieces. 12.000 bm heating and cooling capacity split type AC on each unit. They must have easily changeable filters Copper bose installations for high efficiency All AC units must be min. A+ invertor type Remote controller There must be drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab of floor mounting, Contained within the unit enclosure shall be all factory wing, piping. Consisting of DC compressors, DC fam motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required priorito field start up. Outdoor unit cabinet shall be constructed of galvanized stech (compressor compartment shall be isolated to assure quite operation. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. Condenser coil shall be constructed of aluminum fins mechanically bonded to intermally enhance scameloss copper tubes. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. The heating mode operation temperature should be between (-15-24) °C. Into the one of ward and by a site of 43404 have ER up to 3.8 and a COP up to 4.12. Ourdoor unit should be air cooled split system. Outdoor suits bey adopting plastic case. Plastic fan and Mulit positions airflow volume swith decarcases noise to 4340B(A)	Б	Salit Trans A.C.	
 cooling capacity split type AC on each unit. They must have casily changeable filters Copper hose installations for high efficiency All AC units must be min. A+ invertor type Remote controller There must be drainage system for condensed waters and these drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. Outdoor unit cabinet shall be constructed of galvanized steel; compressors compartment shall be isolated to assure quiet operation. Condenser fans shall be direct drive Propeller type, and motors shall be Herneit type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. Condenser coil shall be torstructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. The heating mode operation temperature should be hertween (-10 ~ 40) °C. Unit will not conting the available of a strather should be a low ambient operation. The tooling the actor science to 4 & 4840(A) in the indoor mit system contor for all units except the operation. The braining mode operation temperature should be hertween (-10 ~ 40) °C. The toutdoor unit should be a low ambient operation. The braining mode operation temperature should be hertween (-10 ~ 40) °C. The outdoor unit should be air coole			
 They must have easily changeable filters Copper house installations for high efficiency All AC units must be min. A+ invertor type Remote controller There must be drainage system for condensed waters and these drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air coled outdoor unit, designed for root, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quite operation. Condenser fans shall be direct drive Propeller type, and motors shall be thermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling eapacity 5 KW which is Scroll DC inverter motor. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless cooper tubes. Unit will not need low ambient or operation in the units should be a low ambient operation. The heating mode operation temperature should be between (-10 ~ 40° C. Unit should have EER up to 3.8 and a COP up to 4.12. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 4840B(A) in the indoor unit. The outdoor fan should be alive object by the should have a Cross Flow fan for uniform distribution. Motors shall be D Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 Copper hose installations for high efficiency All AC units must be min. A+ invertor type Remote controller There must be drainage system for condensed waters and these drainage systems should be cover with channel. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor Contained within the unit enclosure shall be all factory wiring, piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fons, holding therage of R410 Refrigerant and temperature control, filters and special features required plarge of R410 Refrigerant and temperature control, filters and special features required plarge of R410 Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. Condenser roil shall be direct drive Propeller type, and motors shall be totally enclosed. Condenser coil shall be constructed of aluminum fins mechanically bounded to internally enhance seamless copper tubes. Unit will not need low ambient control kit as the operation in the unit should be a low ambient operation. The beating mode operation temperature should be between (-15~24) °C. The tocoling mode operation temperature should be between (-10~40) °C. Unit should have EER up to 3.8 and a COP up to 4.12. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airtitow volume switch decreases noise to 48dB(A) in the indoor unit. The outdoor tan ishould be driven by DC Inverter motor. Unit should have a Cross Flow fan for uniform distribution. Moros shall be D Inverter with multi speed, permanently lubricated with inherent			
 4. All AC units must be min. A+ invertor type 5. Remote controller 6. There must be drainage systems should be cover with channel. 7. The Units should all be factory-assembled and tested, consists of indoor units, each one complete piece, air cooled outdoor of a glavanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor of all units except the unit with cooling eapacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamles copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be hetween (-16 ~ 40)? C. 14. The couldoor unit should be ai cooled split system. Outdoor section shall be crosser to 484B(A) in the indoor unit. 15. The outdoor unit should be air cooled split system. Outdoor section shall be reconsert to the crosses noise to 484B(A) in the indoor unit. 16. The outdoor thin should be air cooled spli			
 6. There must be drainage system for condensed waters and these drainage systems should be cover with channel. 7. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for root, shab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of alaminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-10 - 40) °C. 14. The cooling mode operation temperature should be between (-10 - 40) °C. 15. Unit should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 44Bl(A) in the indoor unit. 17. The outdoor unit should be aircooled split system. Outdoor section shall be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 waters and these drainage systems should be cover with channel. 7. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting. Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special factures required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor fail unitie scept the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance scamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The beating mode operation temperature should be between (-1524) °C. 14. The cooling mode operation temperature should be between (-1524) °C. 15. Unit should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The boutdoor unit, should be aircooled split system. Outdoor shall be driven by DC Inverter motor. 18. The outdoor printaltation. 19. The toutdoor for justallation. 10. The couldoor and should be driven by DC Inverter motor. 11. Outdoor shall be duile for on the ground/root poin shall be driven by DC Inverter motor. 12. Unit should have a Cross Flow fan for uniform distribution	:	5. Remote controller	
 cover with channel. 7. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor units, each one complete piece, air cooled outdoor unit, designed for root, slab of floor mounting, Contained within the unit enclosure shall be all factory witring, piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of alaminom fins mechanically bonded to internally enhance scamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (15 – 24) °C. 14. The cooling mode operation temperature should be between (15 – 46) °C. 15. Unit solud have EER up to 3.8 and a COP up to 4.12. 16. • Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 44BB(A) in the indoor unit. 17. The outdoor unit should be alrowed split system. Outdoor unit should be driven by DC Inverter motor. 18. The outdoor and should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 7. The Units should all be factory-assembled and tested, consists of indoor and outdoor units, each one complete picee, air cooled outdoor unit, designed for roof, slab or floor mounting. Contained within the unit enclosure shall be all factory wiring, piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermstic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-10 - 46) °C. 14. The cooling mode operation temperature should be between (-10 - 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 44BB(A) in the indoor unit. 17. The outdoor unit should be a forwen by DC Inverter motor. 19. Unit should be a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 		• •	
 tested, consists of indoor and outdoor units, each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be thermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (15~24) °C. 14. The cooling mode operation temperature should be between (1-6~40) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be driven by DC lowetter motor. 18. The outdoor fop installation. 18. The outdoor fan should be driven by DC lowetter motor. 20. How the a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 each one complete piece, air cooled outdoor unit, designed for roof, slab or floor mounting, Contained within the unit enclosure shall be all factory wiring, piping, Consisting of DC compressors, DC fam motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. Compressor shall be totally enclosed. Compressor shall be totally enclosed. Compressor shall be totally enclosed. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. Unit will not need low ambient control kit as the operation. The heating mode operation temperature should be between (-15-24) °C. Unit will not need low ambient control kit as the operation. The heating mode operation temperature should be between (-15-24) °C. Unit should have EER up to 3.8 and a COP up to 4.12. Outdoor unit. The outdoor unit. The outdoor unit should be air cooled split system. Outdoor sclic theorem and the for on the ground/root top installation. The outdoor fan should be driven by DC Inverter motor. Unit should have a Cross Flow fan for uniform distribution. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 unit, designed for roof, slab or floor mounting. Contained within the unit enclosure shall be all factory wiring, pijng. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermeit type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15-24) °C. 14. The cooling mode operation temperature should be between (-10 - 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 4&B(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Coss Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 Contained within the unit enclosure shall be all factory wiring, piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient control kit as the operation. 13. The heating mode operation temperature should be between (-10 ~ 46) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise to adapting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor and the diven by DC Inverter motor. 19. Unit should be driven by DC Inverter motor. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 factory wiring. piping. Consisting of DC compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to intermally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 40) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases no ise to 4&dB(A) in the indoor unit. 17. The outdoor unit should be driven by DC Inverter motor. 18. The outdoor for shall be suitable for on the ground/roof top installation. 19. The outdoor for ball be suitable for on the ground/roof top installation. 10. The outdoor flop colored split system. Outdoor section shall be suitable for on the ground/roof top installation. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 compressors, DC fan motor, condensers, evaporator fans, holding charge of R410 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be direct drive Propeller type, and motors shall be direct drive Propeller type, and motors of nall units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 10. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 11. Unit will not need low ambient control kit as the operation. 13. The heating mode operation temperature should be between (-15-24) °C. 14. The cooling mode operation temperature should be between (-10 - 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. • Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be a size noise to the ground/roof top installation. 18. The notidoor nuit should be suitable for on the ground/roof top installation. 19. The outdoor fan and budi be suitable for on the ground/roof top installation. 19. The outdoor and should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 Refrigerant and temperature control, filters and special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-10 - 40) °C. 14. The cooling mode operation temperature should be between (-10 - 40) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 448B(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 special features required prior to field start up. 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15-24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Unit should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor for shall be suitable for on the ground/roof top installation. 20. Motors shall be C Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 8. Outdoor unit cabinet shall be constructed of galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor scient shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 galvanized steel; compressor compartment shall be isolated to assure quiet operation. 9. Condenser fans shall be dired drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-15~24) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. • Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Units should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 be isolated to assure quiet operation. 9. Condenser fans shall be direct drive Propeller type, and motros shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be al vivable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 9. Condenser fans shall be direct drive Propeller type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15-24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be driven by DC Inverter motor. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 type, and motors shall be totally enclosed. 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 10. Compressor shall be Hermetic type, 4 Pole, DC Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 Rotary Inverter motor for all units except the unit with cooling capacity 5 KW which is Scroll DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor for Installation. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 DC inverter motor. 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Unit should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 11. Condenser coil shall be constructed of aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/root top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 aluminum fins mechanically bonded to internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 internally enhance seamless copper tubes. 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 12. Unit will not need low ambient control kit as the operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10~46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 operation in the units should be a low ambient operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 operation. 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 13. The heating mode operation temperature should be between (-15~24) °C. 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16. Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 		-	
 14. The cooling mode operation temperature should be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 be between (-10 ~ 46) °C. 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 15. Units should have EER up to 3.8 and a COP up to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 to 4.12. 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 16 Operation Sound, low noise by adopting plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 plastic case, Plastic fan and Multi positions airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 airflow volume switch decreases noise to 48dB(A) in the indoor unit. 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 17. The outdoor unit should be air cooled split system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 system. Outdoor section shall be suitable for on the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 		48dB(A) in the indoor unit.	
 the ground/roof top installation. 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 18. The outdoor fan should be driven by DC Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 Inverter motor. 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
 19. Unit should have a Cross Flow fan for uniform distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection. 			
distribution. 20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection.			
20. Motors shall be DC Inverter with multi speed, permanently lubricated with inherent overload protection.			
permanently lubricated with inherent overload protection.			
protection.			
Smoore l		protection.	
Specs:		Specs:	

·		1	
	• 22.10.1RPM: 925 - 1085		
	• 22.10.2Capacity (CFM): as shown on the		
	drawings.		
	• 22.10.3Motor Rating: 240V / 50Hz		
	• 22.10.4Motor W: Low – 31.8 High – 38.8		
	• 22.10.5Noise Level (dB): < 40		
F.	Inside Lighting		
	1. All Lights should be heavy duty and decorative		
	LED lighted to use long-life.		
	2. Lights must be Long durability and energy		
	saving option		
	3. There must be Emergency Light option for each		
	room		
	4. There should be sensor when there is no		
	electricity some of lights should be open.		
G .	Storage Areas		
	1. All cabinets locks must be corrosion protected		
	2. Storage cabinets should be high isolated to		
	protect the powder and water leakage		
Н.	Painting		
	1. Min. 3 times epoxy primary coated (corrosion		
	protected);		
	2. All Steel parts shall be Sandblasted to be		
	protected from the corrosion;		
	3. Three times final coating with Epoxy paint.		
	4. Medical examination will be painted in white		
	hue color (TBC), ensuring aesthetically appealing with furniture design		
	5. Remaining rooms will be painted in soft pink		
	hue color (TBC), ensuring aesthetically		
	appealing with furniture design		
	appearing with furniture design		
I.	Electrical Panels and Equipment's		
	1. All electrical cables are fire protected and		
	shielded.		
	2. All electrical and data cables must be jointless,		
	3. Electrical Panels are IP65 protected. Water and		
	Powder protected.		
	4. PLC (Programmable Logic Controller)		
	controlled in the Electrical Panels.		
	5. There should be Phase Control Relay to protect		
	the wrong connection in the Electrical Panels.		
	6. There should be Thermic Magnetic Switch to		
	protect the High Voltage.		
	7. All electronic components should be certified		
	8. There must be external electric connection		
	socket. This socket must be min. IP67		
	Protection level.		
	9. There must be 10-meter extension cable with		
	protection covers		
	10. Rough electrical uses UL listed metal clad 12/2		
	solid copper wires and galvanized metal boxes.		
	11. Universal duplex electrical outlets. Will accept		
	all electrical cords plug-in.		
	12. Outlets and switches are all flush mounted in the walls to assist with infection control.		
	13. GFCI duplex outlet or circuit if an outlet is located within 6 feet of a water source.		
1 1	iocated within 0 feet of a water source.		

	14. Available in 230V, 50/60 Hz options.
	J. Walls and Ceilings
	1. Covered with a 0.55mm full color thickness
	non-FRP washable surface that has been pre-
	laminated to a 3/8" / 1.0 cm
	2. OSB board
	3. OSB board has been treated with an anti-termite
	mineral.
	4. Walls and ceiling are secured using both Liquid Nail Heavy Duty construction adhesive and 1
	¹ /4" dry wall screws.
	K. Internal Floors
	1. All floor surfaces must be made by heavy duty
	steel chassis. There must be reinforcement bars
	and inside equipment fixing points;
	2. All floor surfaces must be cover with min18
	mm marine type plywood; 3. There must be min. 50 mm XPS isolation
	material for all floor surfaces;
	4. All floor surfaces are coated with 2 mm Anti-
	static, Anti-slip safe, washable hospital vinyl
	antibacterial PVC;
	5. There must be min. 7 cm oval skirting all
	around the inside floor corners (anti-bacterial surface);
	6. Aluminum or stainless-steel extruded covers for operational gaps;
	7. All floors should be high isolated to protect the
	powder and water leakages;
	8. Floors should be washable and cleanable.
	9. Armstrong Medley Medical Grade seamless
	vinyl flooring with flash coving.
	L. Sound proofed and climate resilient wall
	1. All walls should be sound proofed and climate
	resilient (tropical climate)
	2. All walls should be high isolated to protect the
	powder and water leakages
	3. Walls should be cleanable
2.	Waiting room with sliding door (non transparent and minimum width: 75 cm for
	wheelchair access and to maintain privacy and confidentiality of other rooms)

2.1	Public sofa/ chair 3 seats - Size depending on final blueprint – approx.: LxWxH = 162x45x68 cm_ - Waiting Chair	Unit	1	
2.2	On Grid Solar power: Solar Panel Capacity: 4 kWp/ 4400 Watt Type: Monocrystalline Conform to the requirement of the installation to the hospital power grid and compatible to the host's EXIM meter ✓Frameless module ✓High Durability Solar Panel ✓Solar Cell Warranty : 25 years ✓Inverter Warranty : 5 years ✓Instalation Warranty : 1 year	Unit	1	

2.3	Working desk	Unit	1	
	Wall folding work desk for administrative work (please see 2D and 3D design for reference). Mounted on sturdy			
	supports; Clearance underneath allows for easy cleaning.			
	Materials: High resistance to corrosion (tropical environment).			
2.4	DISPENSER bottom Gallon, low watt- MODENA	Unit	2	
	DD7302L BIG TANK LOW WATT or others with			
	similar feature			
2.5	Automatic Spray Dispenser Liquid Hand sanitizer 500	Unit	3	
	ml Wall Mounted			
	Interfaced Induction Non-Contact Soup Dependent			
3.	Corridor to examination room and Counsellin	g/ interview ro	om	
		-g,		
		Belie	ve	
	15-95-96 9-5-97 9-5-97	11		
	1.2.4.2.4	y: urs	elf	
	1			
3.1				
	Indoor CCTV	Unit	2	
		Unit	2	
	5MP high performance CMOS -2560 \times 1944 resolution (SUPER HD)	Unit	2	
	5MP high performance CMOS	Unit	2	

3.2	 -Up to 20m IR distance -OSD menu,ICR,AGC,BLC,2D DNR,DWDR -Switchable video output TVI/AHD/CVI/CVBS) -Material : Plastic -Dimensions : 84.6mm × 78.9mm Wall cabinet (Size depending on final blueprint) Wall cabinet for storage (please see 2D and 3D design for reference). Mounted on sturdy supports; Clearance underneath allows for easy cleaning. 	Unit	1	
	Materials: High resistance to corrosion (tropical environment).			
	minimum width: 75 cm for wheelchair acce	ess)		

4.1	Cabinet, instruments, multiple doors depending blue print design and space availability	Package	1	
	Instruments cabinet, multiple door. Mounted on sturdy supports that are height adjustable; the supports are finished with rubber feet or equivalent. Clearance underneath allows for easy cleaning. Inside fixtures facilitate height adjustment of the shelves. Recessed safety glass in the doors allows for viewing cabinet content.			
	Materials: High resistance to corrosion (tropical environment). Doors: with key-lock.			
4.2	Work counter with sink/ wastafel (size depending final blue print, see 2D/ 3D design for reference)	Package	1	
	Work counter to prepare the instruments for sterilization. The counters should be located along the wall of the room			
4.3	Wall folding sofa with cushion (please see 2D and 3D design for reference) Size -depending on final blueprint, approximately 100 cm length and 50 cm width	Unit	1	
4.4	ARISTON ANDRIS2 TOP WIFI 30L 500WATT	Unit	1	
	counter, ensuring proper internet connection during testing and commissioning			
4.5	Wall mirror Size depending on final blueprint, approx: 40 x 150 cm Widht: 3mm	Unit	1	
4.6	Indoor CCTV5MP high performance CMOS-2560 × 1944 resolution (SUPER HD)-Audio : Built-in mic-Lens : 2.8mm-Up to 20m IR distance-OSD menu,ICR,AGC,BLC,2D DNR,DWDR-Switchable video output TVI/AHD/CVI/CVBS)-Material : Plastic-Dimensions : 84.6mm × 78.9mm	Unit	1	

4.7	Blanket, pillow and bed sheet	Package	1	
- ./	Items for the hospital patient bed, mechanical:.	I ackage	1	
	2x Blankets			
	2x Bed sheets			
	2x Pillows			
4.8	Waste bin, with lid and pedal, stainless steel	Unit	2	
4.9	Cot, baby, hospital, with bassinet, on castors	Unit	1	
	Equivalent or similar to:			
	Mobile baby cot with removable bassinet.			
	Mounted on swivel castors, with brakes.			
	With padded mattress, detachable for easy cleaning.			
	Mattress cover removable			
	Basinet sets and removes smoothly from cart frame.			
	Materials:			
	High resistance to corrosion (tropical environment).			
	Mattress: high-density polyurethane foam, or better.			
	Cover: flexible highly tear resistant, anti-static, flame retardant, disinfectant- and liquid proof, washable.			
	retardant, distinct and inquid proof, washable.			
	Frame: 800 x 470 x 900 mm (1 x w x h) approx.			
	Bassinet (bottom): 660 x 400 x 330 mm (l x w x h)			
	approx.			
	Frame, diameter: 30 mm. approx			
	Mattress: 70 mm approx			
4.10	Carrying capacity: 30 kg. Approx Envelope in folio size-@100 pieces	Packs	5	
4.10	Envelope in tono size-@100 pieces	F acks	5	
4.11	Sanitary napkins/ panties:	Packs	10	
	children @10 pieces			
	adults @10 pieces			
4.12	Weight and height scale for adult and childred	Unit	1	
	Maximum weight 120 kg, maximum height 190 cm.			
4.13	Dimension measurement max 150 cm	Unit	2	
	Pengukur Dimensi			
	<u>rengukur Dimensi</u>			
4.14	Grooming kit fit girls/ boys/ women/ men	Unit	1	
	Material: Stainless steel.			
	Nail Clippers: Used for trimming fingernails, toenails,			
	and hangnails			
	Peeling Knives: Used for peeling off the dead and rough skin Cuticle Trimmers: Used for cutting off the cuticle			
	Cuticle Pusher and Nail Cleaner: Curved flat end			
	perfectly pushes the skin back flawlessly and sharp end			
	cuts or scrape away dead cuticle			
	Toe-Nail Nipper: Used for safely clipping off ingrown			
	nails 1 x Toe-Nail Nipper: Used for safely clipping off			
	ingrown nails 1 x Nail File: Used for refining and			
	strengthening sharp and rough nail tips			
	1 x Dead Skin Fork: Used for trimming cuticles with ease in no time			
			1 1	

	 1 x Eyebrow Tweezer: Used for shaping up brows flawlessly by removing all unwanted eyebrow 1 x Eyebrow/Moustache Scissor: Used for cutting and crafting with ease and comfort 1 x Acne Needle with Loop Blackhead: Used for removing blackheads, acne, and various blemishes 1 x Ear Pick: Used for cleaning ear canal or earwax 			
4.15	1 x s LED Ultraviolet UV 400nm 51 LED	Unit	2	

5.	Multi-function room with sliding door (non cm for wheelchair access)	transparent a	nd minimur	n width: 75
5.1	Items for the counselling 1 sofa bed: 1x Sofa bed can be used as Single size Mattress - the mattress should meet the flammability standards and to be made of foam that its designed to reduce interface pressure. Mattress-padding waterproof, washable plastic and flame retardant. An anti-microbial agent to be contained in the surface of the mattress to assist in prohibiting growth of bacteria and fungus. 2x Blankets 2x Bed sheets	Package	1	
5.2	2x Pillows Waste bin, with lid and pedal, stainless steel	Unit	1	
5.3	Custom made wall cabinet with double doors Mounted on sturdy supports; the supports are finished with rubber feet or equivalent. Clearance underneath allows for easy cleaning. Materials: High resistance to corrosion (tropical environment). Doors: with key-lock. Anti bacteria, Anti-rust and anti-mold materials	Package	1	
5.4	Working deskWall folding work desk for administrative work (please see 2D and 3D design for reference). Mounted on sturdy supports; Clearance underneath allows for easy cleaning.Materials: High resistance to corrosion (tropical environment).	Unit	1	
5.5	Chair Size depending on final blue print Approx size: Foot height: 43-53cm Shoulder rest height 50cm Widht: 40cm	Unit	1	
5.6	Stuffed toy Size 15 cm	Unit	2	
5.7	Lego Technic dan Speed Champion Condition : Original in Sealed Box Box Dimension : 16 x 14 x 7 cm.	Package	1	
5.8	Playmate carpet Specs: 1. Soundproofness, ness, waterproofness and heat	Unit	2	

	 preservation; 2. The laying is simple, smooth, and the surface has specific anti-slip properties; 3. The product is odorless and can be used without washing and cooling, providing safe and safe use for babies; 4. ultra-thick thickness prevents baby from falling and being injured when sitting unsteadily while playing on it. It can be used as a gymnastics mat indoors, whi is convenient for storage. Material: EVA plastic foam Size: 120x 60 cm 			
5.9	Wall mounted folding sofa with cushion (please see 2D and 3D design for reference)	Unit	1	
	Size -depending on final blueprint, approximately 130 cm length and 50 cm width			
5.10	Wall Rolled Cartoon wall paper, adjustable, paper changeable (please see 2D/ 3d for reference) approx. size: 100 P x 80 T	Unit	1	
5.11	costum made cabinet with 3 shelfs and top surface	Unit	1	
	adjustable as nursery (changing diaper table)- size and design depends on blueprint			

ANNEX 2: QUOTATION SUBMISSION FORM

Bidders are requested to complete this form, including the Company Profile and Bidder's Declaration, sign it and return it as part of their quotation along with Annex 3: Technical and Financial Offer. The Bidder shall fill in this form in accordance with the instructions indicated. No alterations to its format shall be permitted and no substitutions shall be accepted.

Name of Bidder:	Click or tap here to enter text.	
RFQ reference:	RFQ/UNDP/RESTORE/161300/040/2021 - Moveable GBV center in 40th Container	Date: Click or tap to enter a date.

Company Profile

Item Description	Detail
Legal name of bidder or Lead entity for JVs	Click or tap here to enter text.
Legal Address, City, Country	Click or tap here to enter text.
Website	Click or tap here to enter text.
Year of Registration	Click or tap here to enter text.
Legal structure	Choose an item.
Are you a UNGM registered vendor?	□ Yes □ No If yes, insert UNGM Vendor Number
Quality Assurance Certification (e.g. ISO 9000 or Equivalent) (<i>If</i> <i>yes, provide a Copy of the valid</i> <i>Certificate</i>):	⊠ Yes □ No
Does your Company hold any accreditation such as ISO 14001 or ISO 14064 or equivalent related to the environment? (<i>If yes,</i> <i>provide a Copy of the valid</i> <i>Certificate</i>):	⊠ Yes □ No
Does your Company have a written Statement of its Environmental Policy? (If yes, provide a Copy)	⊠ Yes □ No
Does your organization demonstrate significant commitment to sustainability through some other means, for example internal company policy documents on women empowerment, renewable energies or membership of trade institutions promoting such issues (<i>If yes, provide a Copy</i>)	⊠ Yes □ No
Is your company a member of the UN Global Compact	⊠ Yes □ No
Bank Information	Bank Name: Click or tap here to enter text. Bank Address: Click or tap here to enter text.

	IBAN: Click o	r tap here to ente	er text.	
	SWIFT/BIC: 0	Click or tap here	to enter text.	
	Account Curre	ency: Click or tap	here to enter text.	
	Bank Account	Number: Click	or tap here to enter tex	t.
	Previous rele	vont ovnorionaa	. 3 contracts	
	T Tevious Tele	vant experience	. 5 contracts	
Name of previous contracts	Client & Reference Contact Details including e-mail	Contract Value	Period of activity	Types of activities undertaken
-	Client & Reference Contact Details	Contract	T	
-	Client & Reference Contact Details	Contract	T	

Bidder's Declaration

Yes	No	
		Requirements and Terms and Conditions: I/We have read and fully understand the RFQ, including the RFQ Information and Data, Schedule of Requirements, the General Conditions of Contract, and any Special Conditions of Contract. I/we confirm that the Bidder agrees to be bound by them.
		I/We confirm that the Bidder has the necessary capacity, capability, and necessary licenses to fully meet or exceed the Requirements and will be available to deliver throughout the relevant Contract period.
		Ethics : In submitting this Quote I/we warrant that the bidder: has not entered into any improper, illegal, collusive or anti-competitive arrangements with any Competitor; has not directly or indirectly approached any representative of the Buyer (other than the Point of Contact) to lobby or solicit information in relation to the RFQ ;has not attempted to influence, or provide any form of personal inducement, reward or benefit to any representative of the Buyer.
		I/We confirm to undertake not to engage in proscribed practices, , or any other unethical practice, with the UN or any other party, and to conduct business in a manner that averts any financial, operational, reputational or other undue risk to the UN and we have read the United Nations Supplier Code of Conduct : <u>https://www.un.org/Depts/ptd/about-us/un-supplier-code-conduct</u> and acknowledge that it provides the minimum standards expected of suppliers to the UN.
		Conflict of interest: I/We warrant that the bidder has no actual, potential, or perceived Conflict of Interest in submitting this Quote or entering a Contract to deliver the Requirements. Where a Conflict of Interest arises during the RFQ process the bidder will report it immediately to the Procuring Organisation's Point of Contact.
		Prohibitions, Sanctions: I/We hereby declare that our firm, its affiliates or subsidiaries or employees, including any JV/Consortium members or subcontractors or suppliers for any part of the contract is not under procurement prohibition by the United Nations, including but not limited to prohibitions derived from the Compendium of United Nations Security Council Sanctions Lists and have not been suspended, debarred, sanctioned or otherwise identified as ineligible by any UN Organization or the World Bank Group or any other international Organization.
		Bankruptcy : I/We have not declared bankruptcy, are not involved in bankruptcy or receivership proceedings, and there is no judgment or pending legal action against them that could impair their operations in the foreseeable future.
		Offer Validity Period: I/We confirm that this Quote, including the price, remains open for acceptance for the Offer Validity.
		I/We understand and recognize that you are not bound to accept any Quotation you receive, and we certify that the goods offered in our Quotation are new and unused.
		By signing this declaration, the signatory below represents, warrants and agrees that he/she has been authorised by the Organization/s to make this declaration on its/their behalf.

Signature:

Name: Click or tap here to enter text.

Title: Click or tap here to enter text.

Date: Click or tap to enter a date.

ANNEX 3: TECHNICAL AND FINANCIAL OFFER – WORKS

Bidders are requested to complete this form, sign it and return it as part of their quotation along with Annex 2 Quotation Submission Form. The Bidder shall fill in this form in accordance with the instructions indicated. No alterations to its format shall be permitted and no substitutions shall be accepted.

Name of Bidder:	Click or tap here to enter text.	
RFQ reference:	RFQ/UNDP/RESTORE/161300/040/2021 - Moveable GBV center in 40th Container	Date: Click or tap to enter a date.

Technical Offer

Provide the following:

- a brief description of your qualification and capacity that is relevant to the Scope of Works;
- a brief method statement and implementation plan;
- team composition and CVs of key personnel

Financial Offer

	Description of Works	UoM	Qty	Unit Price	Total Price
	es for producing detailed Engineering Design d 3D), including plumbing and electric int	Package	1		
	es for construction, installation, setting up and ssioning of 3i Moveable GBV Sevice Center:	Package	1		
examin	sions: 1 x 40ft container. Easy access to medical action room and counselling room shall be ed via a corridor/ hallway.				
	oveable GBV center shall be designed to have lowing rooms:				
1. 2. 3.	Waiting room – equipped with folding furniture and enclosed with sliding door to ensure confidentiality of other rooms Medical Examination room Multi functional room for recovery and counselling - multi-functional room to accommodate different needs for recovery and counselling Corridor				
Requi	rements for the container:				
1.					
2.	Container to be coated with medical floors and walls				
3.	Air conditioning				
4.	Ventilation				
5. 6.	Lighting system inside the container Equipped with clean water system conform to Indonesia's health and safety standards				
7.	5				
8. On Gr					

Solar Panel Capacity: 4 kWp/ 4400 Watt		
Type: Monocrystalline		
Conform to the requirement of the installation to the		
hospital power grid and compatible to the host's		
EXIM meter		
✓Frameless module		
✓High Durability Solar Panel		
- ·		
✓Solar Cell Warranty : 25 years		
✓Inverter Warranty : 5 years		
✓Instalation Warranty : 1 year		
A. Clean Water Tank and Waste Water System		
1. Ensure proper system/ connection of clean		
water system and waste water system with the		
host hospital's clean water and waste-water		
system.		
2. 400 liter water tank		
3. $\frac{1}{2}$ hp shallow well water pump - automatic		
water pump for clean water system		
4. 22.75 liter pressure tank		
5. There must be separately pipe installations for		
hot and cold water;		
6. There must be from 30-liter capacity, electrical		
water heater;		
7. There must level gauge and feeding discharging		
valves on the both tanks;		
8. Stainless steel sink (with foot activated faucet,		
no need to touch for water);		
B. Electric water heater:		
Electrical water heater, size 30 L, 1.5 kW electrical		
resistance, wall mounted, 50mm foam insulated, of		
high quality, including wall brackets, price shall		
include all required fittings, accessories, safety		
valve, angle valves, flexible hoses, etc. as per		
engineer's instructions and approval.		
engineer's instructions and approval.		
C. Pipes:		
 Separate pipe installations for cold and hot water. 		
be UPVC, and hot water shall be PPR. Both of pipes and fitting shall conform to SNU		
pipes and fitting shall conform to SNI.		
3. All change in direction in drainage pipes shall		
be gradual and not abrupt.		
4. Installation of plumbing and fitting will follow		
the approved drawing/ blueprint		
5. All pipes shall be plain ended lengths for seal		
ring connection to all fittings.		
6. All pipe jointing and supporting shall be made		
as recommended by the pipe's manufacturer.		
7. All pipes and fittings including adapters,		
couplings and connectors shall be marked with		
the manufacturer name, SNI. number and		
diameter.		

	8.	All exposed pipes shall be provided with		
		suitable paint for climate resilient for tropical		
		climate		
		chinate		
р	G	*4 0° 4		
D.		itary fixtures:		
	1.	All plumbing fixtures shall comply with		
		particular and general specifications and shall		
		be provided with all necessary builders' work		
		material and accessories to enable support and		
		connection.		
	~			
	2.	All items of sanitary ware shall be obtained		
		from a single manufacturer and shall be of 1st		
		class quality without any blemishes, marks,		
		grazing of glaze, chips or the like whatsoever.		
	3.	Install plumbing fixtures and fittings in		
	5.	accordance with the manufacturer's		
		recommendations. Refer to architectural		
		drawings for exact location of fixtures and		
		fittings.		
	4.	All colors for plumbing fixtures, fittings, are		
		subject to the approval of the Engineer.		
-	a 1			
E.	Spli	it Type AC		
	1.	There must be 3 pieces. 12.000 btu heating and		
		cooling capacity split type AC on each unit.		
	2.	They must have easily changeable filters		
	3.	Copper hose installations for high efficiency		
		All AC units must be min. A+ invertor type		
	5.	Remote controller		
	6.	There must be drainage system for condensed		
		waters and these drainage systems should be		
		cover with channel.		
	7.	The Units should all be factory-assembled and		
	<i>.</i> .	tested, consists of indoor and outdoor units,		
		each one complete piece, air cooled outdoor		
		unit, designed for roof, slab or floor mounting,		
		Contained within the unit enclosure shall be all		
		factory wiring, piping, Consisting of DC		
		compressors, DC fan motor, condensers,		
		evaporator fans, holding charge of R410		
		Refrigerant and temperature control, filters and		
		special features required prior to field start up.		
	0			
	8.	Outdoor unit cabinet shall be constructed of		
		galvanized steel; compressor compartment shall		
		be isolated to assure quiet operation.		
	9.	Condenser fans shall be direct drive Propeller		
		type, and motors shall be totally enclosed.		
	10	Compressor shall be Hermetic type, 4 Pole, DC		
	10.	Rotary Inverter motor for all units except the		
		unit with cooling capacity 5 KW which is Scroll		
		DC inverter motor.		
	11.	Condenser coil shall be constructed of		
		aluminum fins mechanically bonded to		
		internally enhance seamless copper tubes.		
	12	Unit will not need low ambient control kit as the		
	14.			
		operation in the units should be a low ambient		
		operation.		
	13.	The heating mode operation temperature should		
		be between $(-15\sim24)$ °C.		

14.	The cooling mode operation temperature should		
	be between $(-10 \sim 46)$ °C.		
15.	Units should have EER up to 3.8 and a COP up		
	to 4.12.		
16.	- Operation Sound, low noise by adopting		
	plastic case, Plastic fan and Multi positions		
	airflow volume switch decreases noise to		
	48dB(A) in the indoor unit.		
17.	The outdoor unit should be air cooled split		
	system. Outdoor section shall be suitable for on		
	the ground/roof top installation.		
18.	The outdoor fan should be driven by DC		
1.0	Inverter motor.		
19.	Unit should have a Cross Flow fan for uniform		
20	distribution.		
20.	Motors shall be DC Inverter with multi speed,		
	permanently lubricated with inherent overload		
	protection.		
	Specs:		
	• 22.10.1RPM: 925 - 1085		
	• 22.10.2Capacity (CFM): as shown on the drawings.		
	 22.10.3Motor Rating: 240V / 50Hz 		
	 22.10.5Woor Rating: 2407 / 5012 22.10.4Motor W: Low – 31.8 High – 38.8 		
	 22.10.5Noise Level (dB): < 40 		
	• 22.10.5101se Level (ub). < 40		
F. Insi	de Lighting		
1.	All Lights should be heavy duty and decorative		
	LED lighted to use long-life.		
2.	Lights must be Long durability and energy		
	saving option		
3.	There must be Emergency Light option for each		
	room		
4.	There should be sensor when there is no		
	electricity some of lights should be open.		
	rage Areas		
1. 2.	All cabinets locks must be corrosion protected Storage cabinets should be high isolated to		
۷.	protect the powder and water leakage		
	protect the powder and water reakage		
H. Pai	nting		
1.	Min. 3 times epoxy primary coated (corrosion		
	protected);		
2.	All Steel parts shall be Sandblasted to be		
	protected from the corrosion;		
3.	Three times final coating with Epoxy paint.		
4.	Medical examination will be painted in white		
	hue color (TBC), ensuring aesthetically		
_	appealing with furniture design		
5.	Remaining rooms will be painted in soft pink		
	hue color (TBC), ensuring aesthetically		
	appealing with furniture design		
L Flee	ctrical Panels and Equipment's		
1 1	All electrical cables are fire protected and		
1.	shielded.		
2.	All electrical and data cables must be jointless,		
3.	Electrical Panels are IP65 protected. Water and		
	Powder protected.		

	4.	PLC (Programmable Logic Controller)		
		controlled in the Electrical Panels.		
	5.	There should be Phase Control Relay to protect		
		the wrong connection in the Electrical Panels.		
	6.	There should be Thermic Magnetic Switch to		
		protect the High Voltage.		
	7.	All electronic components should be certified		
		There must be external electric connection		
		socket. This socket must be min. IP67		
		Protection level.		
	9.	There must be 10-meter extension cable with		
		protection covers		
	10.	Rough electrical uses UL listed metal clad 12/2		
		solid copper wires and galvanized metal boxes.		
	11.	Universal duplex electrical outlets. Will accept		
		all electrical cords plug-in.		
	12.	Outlets and switches are all flush mounted in		
		the walls to assist with infection control.		
	13.	GFCI duplex outlet or circuit if an outlet is		
		located within 6 feet of a water source.		
	14.	Available in 230V, 50/60 Hz options.		
J.	Wa	lls and Ceilings		
	1.	Covered with a 0.55mm full color thickness		
		non-FRP washable surface that has been pre-		
	_	laminated to a 3/8" / 1.0 cm		
		OSB board		
	3.	OSB board has been treated with an anti-termite		
		mineral.		
	4.	Walls and ceiling are secured using both Liquid		
		Nail Heavy Duty construction adhesive and 1		
		¹ / ₄ " dry wall screws.		
17	T 4			
К.		ernal Floors		
	1.	All floor surfaces must be made by heavy duty steel chassis. There must be reinforcement bars		
		and inside equipment fixing points;		
	2.	All floor surfaces must be cover with min18		
	2.	mm marine type plywood;		
	3.	There must be min. 50 mm XPS isolation		
	5.	material for all floor surfaces;		
	4.	All floor surfaces are coated with 2 mm Anti-		
		static, Anti-slip safe, washable hospital vinyl		
		antibacterial PVC;		
	5.	There must be min. 7 cm oval skirting all		
		around the inside floor corners (anti-bacterial		
		surface);		
	6.	Aluminum or stainless-steel extruded covers for		
		operational gaps;		
	7.	All floors should be high isolated to protect the		
		powder and water leakages;		
	8.	Floors should be washable and cleanable.		
	9.	Armstrong Medley Medical Grade seamless		
		vinyl flooring with flash coving.		
		nd proofed and climate resilient wall		
		All walls should be sound proofed and climate		
		resilient (tropical climate)		
	2.	All walls should be high isolated to protect the		
	~	powder and water leakages		
	3.	Walls should be cleanable		

2. Waiting room with sliding door (non transparent and minimum width: 75 cm for wheelchair access and to maintain privacy and confidentiality of other rooms)

access and to maintain privacy and connu	cintianty of ot		15)	
Public sofa/ chair 3 seats	Unit	1		
- Size depending on final blueprint – approx.: LxWxH =				
162x45x68 cm_				
- Waiting Chair				
On Grid Solar power:	Unit	1		
Solar Panel Capacity: 4 kWp/ 4400 Watt				
Type: Monocrystalline				
Conform to the requirement of the installation to the hospital power grid and compatible to the host's				
EXIM meter				
✓Frameless module				
✓ High Durability Solar Panel				
Solar Cell Warranty : 25 years				
✓Inverter Warranty : 5 years				
✓Inverter warranty: 5 years				
• Instalation warranty. Tyear				
Working desk	Unit	1		
····				
Wall folding work desk for administrative work (please				
see 2D and 3D design for reference). Mounted on sturdy				
supports;				
Clearance underneath allows for easy cleaning.				
Materials:				
High resistance to corrosion (tropical environment).				
• • • •	Unit	2		
DISPENSER bottom Gallon, low watt- MODENA	Chit	_		
DD7302L BIG TANK LOW WATT or others with				
similar feature				
and the second se				
	Unit	3		
Automatic Spray Dispenser Liquid Hand sanitizer 500				
ml Wall Mounted				
n IntelSgant Induction Non-Center: Soap Dispenser				
3. Corridor to examination room and Counse	elling/ intervie	w room	•	
Indoor CCTV	Unit	2		
5MP high performance CMOS				
-2560×1944 resolution (SUPER HD)				
-Audio : Built-in mic				
-Lens : 2.8mm				
-Up to 20m IR distance -OSD menu,ICR,AGC,BLC,2D DNR,DWDR				
-Switchable video output TVI/AHD/CVI/CVBS)				
	I			

	•		-	
-Material : Plastic				
-Dimensions : 84.6mm × 78.9mm				
Well askingt (Cine dama ding on final blackwict)	Unit	1		
Wall cabinet (Size depending on final blueprint)	Unit	1		
Wall cabinet for storage (please see 2D and 3D design				
for reference). Mounted on sturdy supports;				
Clearance underneath allows for easy cleaning.				
Materials:				
High resistance to corrosion (tropical environment).				
4. Examination room (middle room) with slid	ling door (non	transpa	arent and mir	nimum width: 75 cm
for wheelchair access)				
Cohinet instrumente multiple decre depending hlue	Dealraga	1 1		
Cabinet, instruments, multiple doors depending blue print design and space availability	Package	1		
print design and space availability				
Instruments cabinet, multiple door.				
Mounted on sturdy supports that are height adjustable;				
the supports are finished with rubber feet or equivalent.				
Clearance underneath allows for easy cleaning.				
Inside fixtures facilitate height adjustment of the				
shelves.				
Recessed safety glass in the doors allows for viewing cabinet content.				
cabillet content.				
Materials:				
High resistance to corrosion (tropical environment).				
Doors: with key-lock.				
Work counter with sink/ wastafel (size depending	Package	1		
final blue print, see 2D/ 3D design for reference)				
Work counter to prepare the instruments for sterilization.				
The counters should be located along the wall of the				
room				
	Unit	1		
Wall folding sofa with cushion (please see 2D and 3D				
design for reference)				
Size -depending on final blueprint, approximately 100				
cm length and 50 cm width ARISTON ANDRIS2 TOP WIFI 30L 500WATT	Unit	1		
ARISTON ANDRISZ TOP WIFT SUL SUUWATT	Unit	1		
ANDRIS2 🛞				
TOP WIFI				
TRANSPORT				
Life time warranty, to be installed close to the work				
counter, ensuring proper internet connection during				
testing and commissioning				
Wall mirror	Unit	1	l	
	Ont	1		
Size depending on final bluenrint approx. A0 x 150 cm		1	1	
Size depending on final blueprint, approx: 40 x 150 cm Widht: 3mm				
Size depending on final blueprint, approx: 40 x 150 cm Widht: 3mm				

5MP high performance CMOS -2560 × 1944 resolution (SUPER HD) -Audio : Built-in mic -Lens : 2.8mm -Up to 20m IR distance -OSD menu,ICR,AGC,BLC,2D DNR,DWDR -Switchable video output TVI/AHD/CVI/CVBS) -Material : Plastic -Dimensions : 84.6mm × 78.9mm				
	D 1	1		
Blanket, pillow and bed sheet Items for the hospital patient bed, mechanical:. 2x Blankets 2x Bed sheets 2x Pillows	Package	1		
Waste bin, with lid and pedal, stainless steel	Unit	2		
Cot, baby, hospital, with bassinet, on castors	Unit	1		-
Equivalent or similar to: Mobile baby cot with removable bassinet. Mounted on swivel castors, with brakes. With padded mattress, detachable for easy cleaning. Mattress cover removable Basinet sets and removes smoothly from cart frame. Materials: High resistance to corrosion (tropical environment). Mattress: high-density polyurethane foam, or better. Cover: flexible highly tear resistant, anti-static, flame retardant, disinfectant- and liquid proof, washable. Frame: 800 x 470 x 900 mm (1 x w x h) approx. Bassinet (bottom): 660 x 400 x 330 mm (1 x w x h) approx. Frame, diameter: 30 mm. approx Mattress: 70 mm approx Carrying capacity: 30 kg. Approx Envelope in folio size-@100 pieces	Packs	5		
Sanitary napkins/ panties:	Packs	10		
children @10 pieces	r acks	10		
adults @10 pieces				
Weight and height scale for adult and childred	Unit	1		
Maximum weight 120 kg, maximum height 190 cm.				
Dimension measurement max 150 cm	Unit	2		
Pengukur Dimensi				
Grooming kit fit girls/ boys/ women/ men	Unit	1		
Material: Stainless steel.				

5. Multi-function room with sliding door (non wheelchair access)	 5. Multi-function room with sliding door (non transparent and minimum width: 75 cm for wheelchair access) 						
1 x s LED Ultraviolet UV 400nm 51 LED	Unit	2					
 Nail Clippers: Used for trimming fingernails, toenails, and hangnails Peeling Knives: Used for peeling off the dead and rough skin Cuticle Trimmers: Used for cutting off the cuticle Cuticle Pusher and Nail Cleaner: Curved flat end perfectly pushes the skin back flawlessly and sharp end cuts or scrape away dead cuticle Toe-Nail Nipper: Used for safely clipping off ingrown nails 1 x Toe-Nail Nipper: Used for refining and strengthening sharp and rough nail tips 1 x Dead Skin Fork: Used for trimming cuticles with ease in no time 1 x Eyebrow Tweezer: Used for shaping up brows flawlessly by removing all unwanted eyebrow 1 x Acne Needle with Loop Blackhead: Used for removing blackheads, acne, and various blemishes 1 x Ear Pick: Used for cleaning ear canal or earwax 							

	.		1	1
Items for the counselling	Package	1		
1 sofa bed:				
1x Sofa bed can be used as Single size Mattress - the				
mattress should meet the flammability standards and to				
be made of foam that its designed to reduce interface pressure. Mattress-padding waterproof, washable plastic				
and flame retardant.				
An anti-microbial agent to be contained in the surface of				
the mattress to assist in prohibiting growth of bacteria				
and fungus.				
2x Blankets				
2x Bed sheets				
2x Pillows				
Waste bin, with lid and pedal, stainless steel	Unit	1		
Custom made wall cabinet with double doors	Package	1		
Mounted on sturdy supports; the supports are finished				
with rubber feet or equivalent.				
Clearance underneath allows for easy cleaning.		1		
Materials:				
High resistance to corrosion (tropical environment).				
Doors: with key-lock. Anti bacteria, Anti-rust and anti-mold materials		1		
Working desk	Unit	1		
working desk	Oint	1		
Wall folding work desk for administrative work (please				
see 2D and 3D design for reference). Mounted on sturdy				
supports;				
Clearance underneath allows for easy cleaning.				
Materials:				
High resistance to corrosion (tropical environment).				
Chair	Unit	1		
Size depending on final blue print Approx size:				
Foot height: 43-53cm				
Shoulder rest height 50cm				
Widht: 40cm				
	Unit	2		
2 m				
		1		
Stuffed toy				
Size 15 cm				
Lego Technic dan Speed Champion	Package	1		
Condition : Original in Sealed Box		1		
, v		1		
Box Dimension : 16 x 14 x 7 cm.				
Playmate carpet	Unit	2		
Specs:		1		
Specs: 1. Soundproofness, ness, waterproofness and heat		1		
preservation;		1		
2. The laying is simple, smooth, and the surface has		1		
specific anti-slip properties;		1		
The second secon		_1	1	

 3. The product is odorless and can be used without washing and cooling, providing safe and safe use for babies; 4. ultra-thick thickness prevents baby from falling and being injured when sitting unsteadily while playing on it. It can be used as a gymnastics mat indoors, whi is convenient for storage. Material: EVA plastic foam Size: 120x 60 cm 			
Wall mounted folding sofa with cushion (please see	Unit	1	
2D and 3D design for reference)			
Size -depending on final blueprint, approximately 130			
cm length and 50 cm width			
Wall Rolled Cartoon wall paper, adjustable, paper	Unit	1	
changeable (please see 2D/ 3d for reference) approx.			
size: 100 P x 80 T			
costum made cabinet with 3 shelfs and top surface	Unit	1	
adjustable as nursery (changing diaper table)- size			
and design depends on blueprint			
Other expenses			
Delivery cost to location			
Other Costs: (please specify)			
Total			

Compliance with Requirements

	You Responses			
	Yes, we will comply	No, we cannot comply	If you cannot comply, pls. indicate counter - offer	
Delivery Lead Time			Click or tap here to enter text.	
Validity of Quotation			Click or tap here to enter text.	
Payment terms			Click or tap here to enter text.	
Other requirements [pls. specify]			Click or tap here to enter text.	

I, the undersigned, certify that I am duly authorized to sign this quotation and bind the company below in event that the quotation is accepted.				
Exact name and address of company	Authorized Signature:			
Company NameClick or tap here to enter text.	Date:Click or tap here to enter text.			
Address: Click or tap here to enter text.	Name:Click or tap here to enter text.			
Click or tap here to enter text.	Functional Title of Authorised			
Phone No.: Click or tap here to enter text.	Signatory: Click or tap here to enter text.			
Email Address: Click or tap here to enter text.	Email Address: Click or tap here to enter text.			