

General Notes

Use only figured dimensions. All drawings to be checked before putting work in

Any discrepancies to be reported to the Consultants. All work to conform to local building regulations and relevant SANS codes of practice. Read in conjuntion with latest revision of all

drawings, schedules and specification.

PARTITIONING LEGEND

(0.6mm Laminated safety glass)

NOTE:

- * Grid line dimensions are to guide installation of partition walls, whereby the centre of the thickness of the partition wall lies within the grid line unless otherwise.
- * Partition walls along grid line (3)&(8) should flush with the duct
- * Door openings to be 900x2100mm

SYSTEM: GYPWALL STANDARD **30 MIN** Rw 42dB

Consisting of 63,5mm UltraSTEEL™ Drywall steel studs inserted at 600mm centres into 63,5mm Drywall steel track at top and bottom and clad both sides with 12,5mm Rhinoboard fixed with 25mm Drywall Streaker screws spaced at 220mm centres. Stagger joints between boards. All joints to be taped and jointed as per manufacturers instructions. 51mm studs and tracks may be used.

> **Headquarters SPV** Contact Details: **Proposed UN Office Development** Plots 236, 237, 248 & 249 **Drawing Title** 1st Floor Office Partitioning

6A 26.03.19

Code Date



ISSUED TO PM

Architects and Planners Corner of Mbhilibhi & Tsekwane St. Mbabane, Swaziland P.O.Box A790 Swazi Plaza H101, Swaziland Tel. +268 404 8515 Fax. +268 404 8513 email. steve.hall@realnet.co.sz

Checked by Date

L(22)01

Purpose of issue as built Project Stage 6: Close Out Drawn by Date Scales **AS SHOWN** Drawing Number Status Revision

