

Specification for Groundnut(peanut) Shell Removing Machine

DESCRIPTION	DETAILS
Quantity	2 (two)
Features	Peanut sheller (single model) are used for shelling the hard cover to get the peanut seeds and its hard cover, the seeds are used for the food or the raw materials for the oil plant. The cover could be pelleted for other purposes. It generally features: Lower energy consumption, Compact design, occupy smaller space and Easy to operate and fix/maintenance
Specifications	<ol style="list-style-type: none"> 1. Portable and easy to install. 2. The screen mesh would be customized/adjustable according to the size of the customer's peanuts, whether it is a large-sized peanut or a small-sized peanut, it can be well shelled without damages 3. High efficiency peeling with adjustable, easygoing of evaded solids impurities/husks with blower separately sorting nut from husks 4. Working fully at three phase electric powering installations 5. Capable of switch-off the machine with power breaker when a malfunctioning/operations and handling 6. Compatible, simple, and user-friendly operating system with the rural community peasant context 7. Simple installing structure 8. Packaged with manuals and assembling guidelines and percussion notifications!!!
Accessories, Spare parts, and Support	<ol style="list-style-type: none"> 1. Supply of essential toolkit required to install, maintain, and operate the machine 2. Supply Installation and Repair Manuals 3. Supply with CD installation training and support 4. Supply a set of the main spare parts with basic tools (adjustable crescent/wrenches/screws/belts/bolt-and-nuts) 5. Quality electrical cables and sockets (with one spare)
Transportation and Packing	The machine must be partially assembled for main and essential components. Proper separate packing and safety standards must apply to avoid damages during transportation and during loading unloading.
Warranty	The manufacturer standard warranty shall be provided and provide the cost of extending the warranty for up to 2 years A confirmation of the machine spare parts availability for 2 years shall be provided
Quality Guarantee Terms	Quality guarantee term is for 2 years. Malfunctions which are caused by machine-self and quality will be responsible for our manufacturer. Other malfunctions which are caused by operation mistakes, man-made problems, etc. will be responsible for clients-self
Performances	Details
Rotary drum length	30
Rotary drum rolling speed	305r/min
Capacity	600-800 kg/h
Motor	2.2kw
Electricity Connection	Three Phase
Air blower speed	1712-1561r/min
Screen frequency	508/min
Breakage	< 3%
Clean rate	>98%
Noise	<85 DB
Size	1291*652*1720mm
Weight	190kg

By: Dereje Zewdu

Date: 23/06/2022

Signature: [Signature]

