Addendum No.1

Title: Procurement of Generator for CPHL and 6 Regional Reference Labs

RFQ Reference: RFQ-007-22

United Nations Development Programmed (UNDP)		
RFQ Reference	Original	Addendum
ANNEX 1:	Supply and Installation of 50 KVA Power	Supply and Installation of 45 KVA Power Generators
SCHEDULE OF	Generators (3Phase)	(3Phase)
REQUIREMENTS	Minimum Rating 50 kVA / 50 kW	Minimum Rating 45 kVA
	Maximum Rating 55 kVA / 55 kW	Maximum Rating 50/56.3 kVA
	Emissions/Fuel Strategy EU Stage IIIA	Emissions/Fuel Strategy EU Stage IIIA emissions
	emissions compliant.	compliant.
	50 Hz Prime 50 kVA / 50 kW	50 Hz Prime 45 kVA
	50 Hz Standby 55 kVA / 55 kW	50 Hz Standby 50 kVA
	60 Hz Prime - / -	60 Hz Prime - / -
	Frequency 50 Hz	Frequency 50/60 Hz
	Speed 1500 RPM	Speed 1500 RPM
	Voltage 220-240 Volts	Voltage 220-240 Volts
	50 Hz Prime Rating Standard reference	50 Hz Prime Rating Standard reference conditions 25C
	conditions 25C (77F) Air Inlet Temp, 100m	(77F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative
	(328 ft) A.S.L. 30% relative humidity.	humidity.
	Fuel consumption data at full load with	Fuel consumption data at full load with diesel fuel with a
	diesel fuel with a specific gravity of 0.85 and	specific gravity of 0.85 and conforming to BS2869: 1998,
	conforming to BS2869: 1998, Class A2.	Class A2.
	Note: the transportation and installation	Note: the transportation and installation cost should be
	cost should be included in the bid price.	included in the bid price.
ANNEX 3:	Supply and Installation of 50 KVA Power	Supply and Installation of 45 KVA Power Generators
TECHNICAL	Generators (3Phase)	(3Phase)
AND FINANCIAL	Minimum Rating 50 kVA / 50 kW	Minimum Rating 45 kVA
OFFER - GOODS	Maximum Rating 55 kVA / 55 kW	Maximum Rating 50/56.3 kVA
	Emissions/Fuel Strategy EU Stage IIIA	Emissions/Fuel Strategy EU Stage IIIA emissions
	emissions compliant.	compliant.
	50 Hz Prime 50 kVA / 50 kW	50 Hz Prime 45 kVA
	50 Hz Standby 55 kVA / 55 kW	50 Hz Standby 50 kVA
	60 Hz Prime - / -	60 Hz Prime - / -
	Frequency 50 Hz	Frequency 50/60 Hz
	Speed 1500 RPM	Speed 1500 RPM
	Voltage 220-240 Volts	Voltage 220-240 Volts
	50 Hz Prime Rating Standard reference	50 Hz Prime Rating Standard reference conditions 25C
	conditions 25C (77F) Air Inlet Temp, 100m	(77F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative
	(328 ft) A.S.L. 30% relative humidity.	humidity.
	Fuel consumption data at full load with	Fuel consumption data at full load with diesel fuel with a
	diesel fuel with a specific gravity of 0.85 and	specific gravity of 0.85 and conforming to BS2869: 1998,
	conforming to BS2869: 1998, Class A2.	Class A2.
	Note: the transportation and installation	Note: the transportation and installation cost should be
	cost should be included in the bid price.	included in the bid price.

Yours sincerely

Head of Procurement UNDP Afghanistan

